


# Data sheet

valid from: 9/30/21



## INSTAFLEX Transition Brass With male thread

Brass: UBA conform  
\* on request



| d<br>(mm) | R<br>(inch) | Code               | SP | Weight<br>(kg) | h<br>(mm) | Remarks          |
|-----------|-------------|--------------------|----|----------------|-----------|------------------|
| 25        | ¾           | <b>760 857 036</b> | 1  | 0.144          | 35        |                  |
| 25        | 1           | <b>760 857 037</b> | 10 | 0.177          | 41        |                  |
| 32        | 1           | <b>760 857 038</b> | 1  | 0.293          | 42        |                  |
| 40        | 1 ¼         | <b>760 857 039</b> | 1  | 0.409          | 44        |                  |
| 50        | 1 ½         | <b>760 857 040</b> | 1  | 0.576          | 47        |                  |
| 63        | 2           | <b>760 857 041</b> | 1  | 1.736          | 32        |                  |
| 75        | 2 ½         | <b>760 857 042</b> | 1  | 2.093          | 37        | without approval |
| *         | 90          | <b>760 857 043</b> | 1  | 2.806          | 32        | without approval |
| *         | 110         | <b>760 857 044</b> | 1  | 3.429          | 38        | without approval |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>