



Pressure pilot valve type PV94 3/2-ways

- For direct installation on single acting pneumatic actuators (FC/F0)
- Hollow screw
- Circuit function C
- Port A: actuator connection
- Port P: compressed air
- Connector plug form C
- Valve material: polyamid/brass

Compressed air connec- tion P	Actuator connec- tion A	Voltage	DN (mm)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)
push-in	G 1/8	230 V, 50-60 Hz	1.0	10	48
push-in	G 1/8	24 V=	1.0	10	48
G 1/8	G 1/8	230 V, 50-60 Hz	1.2	10	48
G 1/8	G 1/8	24 V=	1.2	10	48
NPT 1/8	G 1/8	24 V=	1.0	10	48
NPT 1/8	G 1/8	24 V AC	1.0	10	48
NPT 1/8	G 1/8	110 V, 50-60 Hz	1.0	10	48
push-in	G 1/8	24 V=	1.0	10	48
push-in	G 1/8	24 V, 50-60 Hz	1.0	10	48
push-in	G 1/8	110 V, 50-60 Hz	1.0	10	48
push-in	G 1/8	230 V, 50-60 Hz	1.0	10	48
G 1/8	G 1/8	24 V=	1.2	10	48
G 1/8	G 1/8	24 V, 50-60 Hz	1.2	10	48
G 1/8	G 1/8	110 V, 50-60 Hz	1.2	10	48
G 1/8	G 1/8	230 V, 50-60 Hz	1.2	10	48

NBR Code	SP	Weight (kg)
199 190 571	1	0.133
199 190 573	1	0.130
199 190 572	1	0.126
199 190 574	1	0.187
199 190 546	0	0.118
199 190 561	0	0.177
199 190 547	0	0.173
199 190 510	0	0.177
199 190 511	0	0.180
199 190 512	0	0.184
199 190 513	0	0.178
199 190 498	1	0.172
199 190 499	0	0.175
199 190 500	0	0.117
199 190 501	0	0.117

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>