




COOL-FIT 4.0 Elbow 45° d32-d225

Model:

- Pre-insulated PE100 SDR11, metric
- Insulation made from GF HE foam
- Outer jacket impact resistant. Color: black
- A: Electrofusion Fitting with integrated sealing lip, for a water and vapour tight sealing



DN (mm)	d/D (mm)	SDR	PN (bar)	Code	Weight (kg)	D1 (mm)	L (mm)	L1 (mm)	z (mm)	closest inch (inch)	Type
25	32/90	11	16	738 153 108	0.108	97	72	36	11	1	A
32	40/110	11	16	738 153 109	0.162	117	76	40	11	1 ¼	A
40	50/110	11	16	738 153 110	0.218	117	82	44	13	1 ½	A
50	63/125	11	16	738 153 111	0.315	132	89	48	16	2	A
65	75/140	11	16	738 153 112	0.650	147	98	55	18	2 ½	A
80	90/160	11	16	738 153 113	1.030	168	117	62	30	3	A
90	110/180	11	16	738 153 114	1.270	188	138	72	41	4	A
150	160/250	11	16	738 153 117	4.100	258	161	90	46	6	A
200	225/315	11	16	738 153 120	17.603	324	278	110	143	8	A

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>