





Diaphragm valve type 514 PVC-U With threaded sockets Rp

Model:

- Double flow rate compared to predecessor
- One housing nut replaces four screws
- Handwheel with built-in locking mechanism
- For easy installation and removal
- Short overall length

Option:

- Individual configuration of the valve
- Self adjusting multifunctional module with integrated limit switches
- PN16 available as a configuration

* O-Ring material: FKM

DN (mm)	Thread Type	Size (inch)	d (mm)	PN (bar)	kv-value ($\Delta p=1$ bar) (L/min)	NBR Code	SP	Weight (kg)
15	Rp	½	20	10	125	161 514 402	1	0.400
20	Rp	¾	25	10	271	161 514 403	1	0.523
25	Rp	1	32	10	481	161 514 404	1	0.678
32	Rp	1 ¼	40	10	759	161 514 405	1	1.429
40	Rp	1 ½	50	10	1263	161 514 406	1	2.528
50	Rp	2	63	10	1728	161 514 407	1	3.449

EPDM Code	SP	Weight (kg)	PTFE/ EPDM* Code	SP	Weight (kg)	FKM Code	SP	Weight (kg)
161 514 412	1	0.298	161 514 432	1	0.410	161 514 462	1	0.400
161 514 413	1	0.426	161 514 433	1	0.534	161 514 463	1	0.523
161 514 414	1	0.679	161 514 434	1	0.693	161 514 464	1	1.163
161 514 415	1	0.957	161 514 435	1	1.449	161 514 465	1	1.429
161 514 416	1	1.654	161 514 436	1	2.558	161 514 466	1	2.528
161 514 417	1	3.449	161 514 437	1	3.477	161 514 467	1	3.449

D (mm)	D2 (mm)	D3 (mm)	H (mm)	H1 (mm)	H2 (mm)	L (mm)	L2 (mm)	M	z (mm)	Lift = Hx (mm)
65	65	43	73	14	12	128	25	M6	96	7
80	65	51	81	18	12	152	25	M6	114	10
88	87	58	107	22	12	166	25	M6	122	13
101	87	72	115	26	15	192	45	M8	140	15
117	135	83	148	32	15	222	45	M8	160	19
144	135	100	166	39	15	266	45	M8	190	25

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>