



Flange adaptor PVC-U Joining face with O-ring groove metric

Model:

- Solvent cement socket metric
- Counterpart: flange adaptor flat code no. 721 800 105-721 790 111-125, combined flange adaptor (d160, d200, d225, d280, d315)
- Gasket: O-ring EPDM code no. 748 410 000-176, FKM code no. 749 410 000-176
- Flange: PVC-U code no. 721 700 005-138, PP/steel code no. 727 700 206-223, PP-V for socket systems metric code no. 727 700 406-423

d (inch)	d (mm)	DN (mm)	PN (bar)	Code	SP	Weight (kg)	D1 (mm)	z (mm)	D (mm)	L (mm)	L1 (mm)
	16	10	16	721 810 105	10	0.008	29	6	22	20	9
	20	15	16	721 810 106	10	0.011	34	6	27	22	9
	25	20	16	721 810 107	10	0.018	41	6	33	25	10
	32	25	16	721 810 108	10	0.027	50	6	41	28	10
	40	32	16	721 810 109	10	0.046	61	8	50	34	13
	50	40	16	721 810 110	10	0.068	73	8	61	39	13
	63	50	16	721 810 111	10	0.120	90	8	77	46	14
2 ½	75	65	16	721 810 112	10	0.183	106	8	91	52	15
	90	80	16	721 810 113	10	0.286	125	10	108	61	16
	110	100	16	721 810 114	10	0.478	150	11	131	72	18
	125	100	16	721 810 115	5	0.607	170	11	148	80	19
5	140	125	16	721 810 116	6	0.804	188	11	165	87	20
	160	150	16	721 810 117	2	1.226	213	11	188	97	22
	200	200	10	721 810 119	2	1.593	250	12	224	118	30
	225	200	10	721 810 120	2	1.878	274	12	248	131	31
	250	250	10	721 810 121	1	2.175	303	9	274	140	23
	280	250	10	721 810 122	1	3.170	329	13	308	158	30
	315	300	6	721 810 123	1	4.891	379	17	346	180	35

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>