



Type 3519 Flow Wet-Tap Valve

Flow:

- Installs into pipe sizes: DN15 to DN900, 0.5 to 36 in
- Material: PVC body, seals FKM or EPDM
- Max Pressure rating: 7 bar @ 20 °C, (100 psi @ 68 °F)
- Standard: FKM O-rings (EPDM or FFKM on request)
- Other materials of rotor and axis on request

MFR #	Description	Pipe Size (inch)	DN-DN (mm)
3-3519	Wet-Tap Valve only	-0	-
P51530-P3	Polypro extended length paddlewheel sensor	0.5 - 4.0	
3-2536-P3	Polypro extended length low flow paddlewheel sensor	0.5 - 4.0	
P51530-P4	Polypro extended length paddlewheel sensor	5.0 - 8.0	
3-2536-P4	Polypro extended length low flow paddlewheel sensor	5.0 - 8.0	
P51530-P5	Polypro extended length paddlewheel sensor	10.0 - 36.0	
3-2536-P5	Polypro extended length low flow paddlewheel sensor	10.0 - 36.0	

Code	DN-DN* (mm)
159 000 757	
198 840 310	15-100
159 000 758	15-100
198 840 311	125-200
159 000 759	125-200
198 840 312	250-900
159 000 760	250-900

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>