# **VALVES SERIES PEV** PEDAL OPERATED

- The valves series PEV with pedal are available in a wide range:

   5/2 1/4" monostable and bistable with guarded pedal

   3/2 M5 monostable, pedal not guarded

   3/2 Ø 4 monostable, pedal not guarded


   3/2 M5 in monostable and bistable configuration with guarded pedal


   3/2 Ø 4 in monostable and bistable configuration with guarded pedal



| TECHNICAL DATA  |              |  |                        |                        |
|---|--------------|--|------------------------|------------------------|
| Valve fitting port  |              | Ø 4  | M5                     | 1/4"                   |
| Туре  |              | Mono/ bistable guarded   | Monostable not guarded | Mono/ bistable guarded |
|   |              | Monostable not guarded   | Mono/ bistable guarded | -                      |
| Operating pressure  | bar          |  | 2.5 to 10              |                        |
|   | Мра          |  | 0.25 to 1              |                        |
|   | psi          |  | 36 to 145              |                        |
| Operating temperature range                                     | °C           |  | -10 + 60               |                        |
| Nominal diameter  | mm           | 2.5  | 2.5                    | 7.5                    |
| Conductance C   | NI/min · bar | 16.5   | 16.5                   | 264.26                 |
| Critical ratio b  | bar/bar      | 0.03   | 0.03                   | 0.32                   |
| Flow rate at $6.3\ \text{bar}\ \Delta\text{P}\ 0.5\ \text{bar}$ | NI/min       | 60   | 60                     | 640                    |
| Flow rate at 6.3 bar ΔP 1 bar                                   | NI/min       | 95   | 95                     | 840                    |
| Fluid   |              | Filtered air without lubrication; lubrication, if used, must be co |                        | , must be continuous   |
| Compatibility with oils   |              | See <b>chapter Z1</b>  |                        |                        |
|   |              |  |                        |                        |
|   |              |  |                        |                        |
|   |              |  |                        |                        |
|   |              |  |                        |                        |
|   |              |  |                        |                        |
|   |              |  |                        |                        |
|   |              |  |                        |                        |


#### **FLOW CHARTS**








# GUARDED PEDAL WITH VALVES 5/2 1/4" - 3/2 M5 - 3/2 Ø 4



|   | Symbol  | Code        | Description            | Abbrev.       | Weight [g] |
|---|---|-------------|------------------------|---------------|------------|
|   |   | W3120000001 | 5/2 - 1/4" monostable, | PEV 35 PES PR | 1027       |
|   |   |             | guarded                |               |            |
|   | A T W   | W3120000011 | 5/2 - 1/4" bistable,   | PEV 35 PEB PR | 1035       |
|   |   |             | guarded •              |               |            |
|   |   | W3120000301 | 3/2 M5 monostable,     | PEV 03 PES PR | 883        |
|   |   |             | guarded                |               |            |
|   |   | W3120000321 | 3/2 Ø 4 monostable,    | PEV F3 PES PR | 887        |
|   |   |             | guarded                |               |            |
|   | <u>/</u>  | W3120000331 | 3/2 M5 bistable,       | PEV 03 PEB PR | 890        |
|   |   |             | guarded •              |               |            |
|   |   | W3120000311 | 3/2 Ø 4 bistable,      | PEV F3 PEB PR | 914        |
|   |   |             | guarded •              |               |            |
|   |   | W3120000021 | 5/2 - 1/4" monostable, | PEV 35 PEC PR | 1014       |
|   |   |             | with mechanical block  |               |            |
|   |   |             | and guarden ■          |               |            |
| <ul> <li>The pedal-down position is maintained by a lever.</li> </ul> |   |             |                        |               |            |
|   | W/h = th = f = t = 0 = th = l = d = l = l = d = l = d = l = d = l = d = l = d = l = d = l = d = l = d = l = d = l = |             |                        |               |            |

- When the foot presses on the lever, the pedal releases and can rise.
  - When the foot presses on a locking lever, the pedal can be lowered.

### NOT-GUARDED PEDAL WITH VALVES 3/2 M5 - 3/2 Ø 4



| Symbol           | Code        | Description          | Abbrev.       | Weight [g] |
|------------------|-------------|----------------------|---------------|------------|
| 2                | W3120000411 | 3/2 - M5 monostable, | PEV 03 PES WP | 188        |
| J—(T 11 √3 1 VVV |             | not guarded          |               |            |
|                  | W3120000401 | 3/2 Ø 4 monostable,  | PEV F3 PES WP | 192        |
|                  |             | not guarded          |               |            |
|                  |             |                      |               |            |
|                  |             |                      |               |            |

## SYNOPTIC, SIZES AND VERSIONS

| PEV                         | F                           | 3                                  | PE                | С  | W P   |
|-----------------------------|-----------------------------|------------------------------------|-------------------|--|---|
| FAMILY                      | DIMENSIONS                  | FUNCTION                           | OPERATORS 14      | RESETTING (12)   | FURTHER DETAILS                             |
| FAMILY PEV valve with pedal | DIMENSIONS 3 1/4 0 M5 F Ø 4 | <b>FUNCTION 3</b> 3/2 <b>5</b> 5/2 | PE pedal operated | RESETTING (12)  S mechanical springs C mechanical block B bistable | FURTHER DETAILS  WP not guarded  PR guarded |
|                             |                             |                                    |                   |  |   |