



Socket PVC-U Rp

Model:

- With parallel female thread Rp
- Connection to plastic thread only
- Do not use thread sealing pastes that are harmful to PVC-U
- Install with low mechanical stress and avoid large cyclic temperature changes

Thread Type	Size (inch)	PN (bar)	Code	SP	Weight (kg)	z (mm)	L (mm)	s (mm)
Rp	¼	10	721 910 604	10	0.010	7	27	22
Rp	⅜	10	721 910 605	10	0.015	7	29	27
Rp	½	10	721 910 606	10	0.024	9	35	32
Rp	¾	10	721 910 607	10	0.029	9	39	36
Rp	1	10	721 910 608	10	0.053	11	45	46
Rp	1 ¼	10	721 910 609	10	0.076	11	49	55
Rp	1 ½	10	721 910 610	10	0.106	11	49	65
Rp	2	10	721 910 611	5	0.180	11	57	80

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>