


## Reduced tee 90° PVC-U metric

# additional bag containing 100 pieces (10 bags of 10 pieces)



#	d - d1 (mm)	PN (bar)	Code	SP	Weight (kg)	Z1 (mm)	Z2 (mm)	L1 (mm)	L2 (mm)	E2 (mm)	E1 (mm)
	20 - 16	16	<b>RV0TRI20A</b>	10	0.024	11	11	16	14	23	28
	25 - 16	16	<b>RV0TRI25A</b>	10	0.039	14	14	19	14	23	34
	25 - 20	16	<b>RV0TRI25B</b>	10	0.040	14	14	19	16	28	34
	32 - 16	16	<b>RV0TRI32A</b>	10	0.063	17	17	22	14	23	42
	32 - 20	16	<b>RV0TRI32B</b>	10	0.068	17	17	22	16	28	42
	32 - 25	16	<b>RV0TRI32C</b>	10	0.068	17	17	22	19	34	42
	40 - 20	16	<b>RV0TRI40B</b>	100	0.107	21	21	26	16	28	51
	40 - 25	16	<b>RV0TRI40C</b>	100	0.108	21	21	26	19	34	51
	40 - 32	16	<b>RV0TRI40D</b>	100	0.112	21	21	26	22	42	51
	50 - 20	16	<b>RV0TRI50B</b>	50	0.155	26	26	31	16	28	61
	50 - 25	16	<b>RV0TRI50C</b>	50	0.160	26	26	31	19	34	61
	50 - 32	16	<b>RV0TRI50D</b>	50	0.161	26	26	31	22	42	61
	50 - 40	16	<b>RV0TRI50E</b>	50	0.173	26	26	31	26	51	61
	63 - 20	16	<b>RV0TRI63B</b>	30	0.257	33	33	38	16	28	75
	63 - 25	16	<b>RV0TRI63C</b>	30	0.262	33	33	38	19	34	75
	63 - 32	16	<b>RV0TRI63D</b>	30	0.274	33	33	38	22	42	75
	63 - 40	16	<b>RV0TRI63E</b>	30	0.270	33	33	38	26	51	75
	63 - 50	16	<b>RV0TRI63F</b>	30	0.278	33	33	38	31	61	75
	75 - 32	16	<b>RV0TRI75D</b>	18	0.455	39	39	44	22	42	89
	75 - 40	16	<b>RV0TRI75E</b>	45	0.460	39	39	44	26	51	89
	75 - 50	16	<b>RV0TRI75F</b>	18	0.458	39	39	44	31	61	89
	75 - 63	16	<b>RV0TRI75G</b>	30	0.471	39	39	44	38	75	89
	90 - 40	16	<b>RV0TRI90E</b>	30	0.692	47	47	51	26	61	106
	90 - 50	16	<b>RV0TRI90F</b>	28	0.703	47	47	51	31	61	106
	90 - 63	16	<b>RV0TRI90G</b>	24	0.707	47	47	51	38	75	106
	90 - 75	16	<b>RV0TRI90H</b>	24	0.731	47	47	51	44	89	106
	110 - 50	16	<b>RV0TRI91F</b>	16	1.228	57	57	61	31	61	129
	110 - 63	16	<b>RV0TRI91G</b>	16	1.231	57	57	61	38	75	129
	110 - 75	16	<b>RV0TRI91H</b>	16	1.245	57	57	61	44	89	129
	110 - 90	16	<b>RV0TRI91I</b>	14	1.302	57	57	61	51	106	129
	125 - 63	16	<b>RV0TRI92G</b>	9	1.955	66	66	69	38	75	148
	125 - 90	16	<b>RV0TRI92I</b>	9	1.737	66	66	69	51	106	148
	125 - 110	16	<b>RV0TRI92L</b>	8	1.827	66	66	69	61	129	148
	160 - 90	16	<b>RV0TRI94I</b>	4	3.771	82	82	86	51	106	190
	160 - 110	16	<b>RV0TRI94L</b>	4	3.819	82	82	86	61	129	190

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>