



Multi/Clamp Saddle Studs threaded outlet 3/4

Model:

- Saddle with threaded outlet
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)
- Outlet dimension up to 4" available on request
- Lower shell half is without gasket (available on request)
- Other sizes available on request
- Not suitable for the use on plastic pipes
- Water and gas: NBR according to EN 682 (-10°C up to +70°C); potable water: EPDM according to EN 681-1 (-10°C up to +55°C)
- For working pressures in GAS please consult Georg Fischer Waga N.V.

Range (mm)	PN Water (bar)	NBR Code
68 - 78	16.0	724 201 062
88 - 110	16.0	724 201 074
108 - 134	16.0	724 201 098
133 - 155	16.0	724 201 134
159 - 181	16.0	724 201 170
168 - 190	16.0	724 201 194
190 - 212	16.0	724 201 206
216 - 238	16.0	724 201 218
238 - 260	16.0	724 201 242
267 - 289	16.0	724 201 254

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>