



Iron Strap-on saddle

- Up to 8 in. - PVDF insert, over 8 in. - PVC insert
- C - Clearance dimension
- Buna Nitrile O-ring
- For use with SCH 80 & 40 metal pipe (ASTM)
- PTFE tape wetted material. Consult factory for available options.

Type	Size (inch)	H (inch)	o.d. min (inch)	o.d. max (inch)	C (inch)	Sensor Type	Code	Weight (kg)
IR8S020	2.00	5.50	2.35	2.56	1.44	Flow -X0, pH -XX	198 801 425	1.390
IR8S025	2.50	5.50	2.44	2.91	1.44	Flow -X0, pH -XX	198 801 426	5.000
IR8S030	3.00	6.50	2.97	3.54	1.44	Flow -X0, pH -XX	198 801 427	2.100
IR8S040	4.00	7.50	4.40	4.55	1.44	Flow -X0, pH -XX	198 801 420	1.000
IR8S050	5.00	9.00	5.00	5.63	2.25	Flow -X1	198 801 429	5.000
IR8S060	6.00	10.50	5.94	6.70	2.25	Flow -X1	198 801 430	5.000
R8S080	8.00	12.00	7.69	8.72	2.25	Flow -X1	198 801 431	4.200
IR8S100	10.00	18.00	10.64	12.12	2.25	Flow -X2	198 801 432	6.300
IR8S120	12.00	20.00	12.62	14.32	2.25	Flow -X2	198 801 433	7.200

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>