

COMP. PNEUMATIQUES - Raccords

Traversée de cloison BSPP Femelle



Ø Racc.	Référence	Ø Ext.	Epaisseur Max.	Clé
		(mm)		
G1/8"	E230L001	M16 x 1,5	10	22
G1/4"	E230L002	M20 x 1,5	16	27
G3/8"	E230L003	M26 x1,5	15	32
G1/2"	E230L004	M28 x 1,5	21	36
G3/4"	E230L005	M33 x 1,5	22,5	41
G1"	E230L006	M42 x 1,5	24,5	46
G1 1/4"	E230L007	M48 x 1,5	29,5	55

Embout cannelé avec O-ring NBR - BSPP Mâle



Ø Racc.	Ø int. tube	Référence
G1/8"	7 mm	2119001
	8 mm	2119003
	9 mm	2119004
G1/4"	7 mm	2119002
	9 mm	2119005
	12 mm	2119007
G3/8"	9 mm	2119006
	12 mm	2119008
	17 mm	2119010
G1/2"	12 mm	2119009
	17 mm	2119011

Bouchon cylindrique avec O-ring NBR - BSPP Mâle



Ø Racc.	Référence
M5	2107000
G1/8"	2107001
G1/4"	2107002
G3/8"	2107003
G1/2"	2107004
G3/4"	Z408000018
G1"	Z408000019

Bonnet cylindrique - BSPP Femelle



Ø Racc.	Référence
G1/8"	2108001
G1/4"	2108002
G3/8"	2108003
G1/2"	2108004

Remarque : Tout autre modèle disponible sur demande.