


PROGEF Plus silicone free
Check valve type 562
With socket fusion spigots metric

Model:

- Material: PP-H / silicone free cleaned
- For horizontal or vertical installation
- Sealing at a minimum water column of 1 m
- Spring loaded, spring made of stainless steel (1.4310)
- Spring available in other materials, see spare parts
- Designed for easy installation and removal
- Vibration free even at high flow velocity
- Flow-optimized return cone, double guided
- Compact installation length, same as ball valve type 546
- Z-length, end connectors and union nuts **not** compatible with type 360
- New DN65-DN100



d (mm)	DN (mm)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)	EPDM Code	SP	Weight (kg)	FKM Code	SP	Weight (kg)
16	10	10	190	167 562 221	1	0.080	167 562 231	1	0.080
20	15	10	180	167 562 222	1	0.090	167 562 232	1	0.090
25	20	10	380	167 562 223	1	0.170	167 562 233	1	0.190
32	25	10	460	167 562 224	1	0.200	167 562 234	1	0.200
40	32	10	850	167 562 225	1	0.340	167 562 235	1	0.350
50	40	10	1080	167 562 226	1	0.510	167 562 236	1	0.510
63	50	10	1670	167 562 227	1	0.940	167 562 237	1	0.950
75	65	10	2950	167 562 228	1	2.360	167 562 238	1	2.370
90	80	10	3600	167 562 229	1	3.730	167 562 239	1	3.750
110	100	10	4150	167 562 230	1	5.960	167 562 240	1	5.980

d (mm)	D (mm)	L (mm)	L2 (mm)	closest inch (inch)
16	50	110	56	$\frac{3}{8}$
20	50	120	56	$\frac{1}{2}$
25	58	139	65	$\frac{3}{4}$
32	68	150	71	1
40	84	170	85	1 $\frac{1}{4}$
50	97	190	89	1 $\frac{1}{2}$
63	124	220	101	2
75	166	280	136	2 $\frac{1}{2}$
90	200	296	141	3
110	238	336	164	4

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>