



Solenoid pilot valve type PV94 Accessory

Model:

- Cable plug to DIN EN 175301 - 8203 (DIN 43 650)

Cable plug form	Voltage	Version	NBR Code	SP	Weight (kg)
B	0-250 V	no circuitry	199 190 578	1	0.048
B	0-24 V	with LED	199 190 579	1	0.020
B	0-250 V	with LED	199 190 580	1	0.020
B	0-24 V	with rectifier LED	199 190 581	1	0.020
C	0-250 V	no circuitry	199 190 518	0	0.010
C	0-24 V	with LED	199 190 519	0	0.015
C	0-24 V	with LED and varistor	199 190 520	0	0.015
C	0-24 V	with rectifier LED and varistor	199 190 521	0	0.020
C	200-240 V	with LED	199 190 522	0	0.020
C	200-240 V	with LED and varistor	199 190 523	0	0.020

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>