

Data sheet

valid from: 9/8/18



Type 2540 Stainless Steel Standard

Flow:

- *Recommended 198 820 008 (3-1500.663) Hot Tap installation tool (sold separately)
- Installs into pipe sizes: DN40 to DN600, 1.5 to 24 in
- Operating range: 0.1 to 6 m/s, 0.3 to 20 ft/s
- Max Pressure rating: 17 bar @ 100 °C, 250 psi @ 212 °F Optional EPDM: 17 bar @ 82 °C, 250 psi @ 180 °F
- Power source: 5 to 24V DC, 1.5mA max
- Compatibility: 8900, 9900, 9900-1BC, 9950

MFR #	Mounting	Rotor Pin	Code
3-2540-1	1.5 in. NPT thread	Tungsten Carb.	198 840 035
3-2540-2	1.5 in. ISO thread	Tungsten Carb.	198 840 036
3-2540-1S	1.5 in. NPT thread	Stainless Steel	159 001 501
3-2540-2S	1.5 in. ISO thread	Stainless Steel	159 001 502

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>