



Check valve type 562 ABS
With solvent cement sockets metric

Model:

- For horizontal or vertical installation
- Sealing at a minimum water column of 1 m
- Spring loaded, spring made of stainless steel (1.4310)
- Spring available in other materials, see spare parts
- Designed for easy installation and removal
- Vibration free even at high flow velocity
- Flow-optimized return cone, double guided
- Compact installation length, same as ball valve type 546
- Z-length, end connectors and union nuts **not** compatible with type 360
- New DN65-DN100

d (mm)	DN (mm)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)	EPDM Code	SP	Weight (kg)	D (mm)	L (mm)	L2 (mm)	z (mm)	closest inch (inch)
16	10	10	190	169 562 001	1	0.090	50	92	56	64	3/8
20	15	10	180	169 562 002	1	0.090	50	95	56	64	1/2
25	20	10	380	169 562 003	1	0.190	58	110	65	72	3/4
32	25	10	460	169 562 004	1	0.220	68	123	71	79	1
40	32	10	850	169 562 005	1	0.380	84	146	85	94	1 1/4
50	40	10	1080	169 562 006	1	0.560	97	157	89	95	1 1/2
63	50	10	1670	169 562 007	1	0.990	124	183	101	107	2
75	65	10	2950	169 562 008	1	2.420	166	233	136	144	2 1/2
90	80	10	3600	169 562 009	1	3.870	200	254	141	151	3
110	100	10	4150	169 562 010	1	6.240	238	301	164	174	4

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>