

## 8.2. Raccords "push-on"

### 8.2.1. Corps en laiton nickelé

LAITON

#### Caractéristiques :

- Pression d'utilisation : -0,99 à 18 bar
- Température de service du fluide : -10°C à +80°C

#### Piquage droit conique - BSPT Mâle



| Ø ext. tube | Ø int. tube | Ø Racc. | Référence     |
|-------------|-------------|---------|---------------|
| 4 mm        | 2 mm        | R1/8"   | FINB.021.0402 |
| 5 mm        | 3 mm        | R1/8"   | 2301017       |
| 6 mm        | 4 mm        | R1/8"   | 2301001       |
|             |             | R1/4"   | 2301002       |
| 8 mm        | 6 mm        | R1/8"   | 2301003       |
|             |             | R1/4"   | 2301004       |
|             |             | R3/8"   | 2301005       |
| 10 mm       | 8 mm        | R1/4"   | 2301006       |
|             |             | R3/8"   | 2301007       |
|             |             | R1/2"   | 2301008       |
| 12 mm       | 10 mm       | R3/8"   | 2301009       |
|             |             | R1/2"   | 2301010       |
| 15 mm       | 12,5 mm     | R1/2"   | 2301015       |

#### Union double égal



| Ø ext. tube | Ø int. tube | Référence     |
|-------------|-------------|---------------|
| 4 mm        | 2 mm        | FINB.022.0402 |
| 6 mm        | 4 mm        | 2303001       |
| 8 mm        | 6 mm        | 2303002       |
| 10 mm       | 8 mm        | 2303003       |
| 12 mm       | 10 mm       | 2303004       |

#### Traversée de cloison union



| Ø ext. tube | Ø int. tube | Référence |
|-------------|-------------|-----------|
| 6 mm        | 4 mm        | 2304001   |
| 8 mm        | 6 mm        | 2304002   |
| 10 mm       | 8 mm        | 2304003   |
| 12 mm       | 10 mm       | 2304004   |

#### Piquage droit cylindrique - BSPP Mâle + O-ring



| Ø ext. tube | Ø int. tube | Ø Racc. | Référence |
|-------------|-------------|---------|-----------|
| 4 mm        | 2 mm        | M5      | 2351001   |
| 6 mm        | 4 mm        | M5      | 2351002   |
|             |             | G1/8"   | 2351003   |
|             |             | G1/4"   | 2351004   |
| 8 mm        | 6 mm        | G1/8"   | 2351005   |
|             |             | G1/4"   | 2351006   |
|             |             | G3/8"   | 2351007   |
| 10 mm       | 8 mm        | G1/4"   | 2351008   |
|             |             | G3/8"   | 2351009   |
|             |             | G1/2"   | 2351010   |
| 12 mm       | 10 mm       | G3/8"   | 2351011   |
|             |             | G1/2"   | 2351012   |

#### Coude conique - BSPT Mâle



| Ø ext. tube | Ø int. tube | Ø Racc. | Référence     |
|-------------|-------------|---------|---------------|
| 4 mm        | 2 mm        | R1/8"   | FINB.023.0402 |
| 5 mm        | 3 mm        | R1/8"   | 2305016       |
| 6 mm        | 4 mm        | R1/8"   | 2305001       |
|             |             | R1/4"   | 2305002       |
| 8 mm        | 6 mm        | R1/8"   | 2305003       |
|             |             | R1/4"   | 2305004       |
|             |             | R3/8"   | 2305005       |
| 10 mm       | 8 mm        | R1/4"   | 2305006       |
|             |             | R3/8"   | 2305007       |
|             |             | R1/2"   | 2305008       |
| 12 mm       | 10 mm       | R3/8"   | 2305009       |
|             |             | R1/2"   | 2305010       |
| 15 mm       | 12,5 mm     | R1/2"   | 2305017       |

#### Piquage droit cylindrique - BSPP Femelle



| Ø ext. tube | Ø int. tube | Ø Racc. | Référence |
|-------------|-------------|---------|-----------|
| 6 mm        | 4 mm        | G1/8"   | 2302001   |
|             |             | G1/4"   | 2302002   |
|             |             | G3/8"   | 2302012   |
| 8 mm        | 6 mm        | G1/4"   | 2302003   |
|             |             | G3/8"   | 2302004   |
|             |             | G1/8"   | 2302005   |
| 10 mm       | 8 mm        | G1/4"   | 2302006   |
|             |             | G3/8"   | 2302007   |
|             |             | G1/2"   | 2302008   |

#### Coude non orientable cylindrique - BSPP Femelle



| Ø ext. tube | Ø int. tube | Ø Racc. | Référence |
|-------------|-------------|---------|-----------|
| 6 mm        | 4 mm        | G1/8"   | 2352001   |
| 8 mm        | 6 mm        | G1/4"   | 2352002   |