



Adaptor socket nipple PVC-C metric R

Model:

- With solvent cement spigot/socket metric and taper male thread R
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC-C

d (mm)	Thread Type	Size (inch)	d1 (mm)	PN (bar)	Code	SP	Weight (kg)	z (mm)	z1 (mm)	s (mm)
16	R	½	20	16	723 910 556	10	0.017	42	28	32
20	R	¾	25	16	723 910 557	10	0.026	47	31	36
25	R	1	32	16	723 910 558	10	0.043	54	35	46
32	R	1 ¼	40	16	723 910 559	10	0.065	60	38	55
40	R	1 ½	50	16	723 910 560	10	0.102	66	40	65
50	R	2	63	16	723 910 561	5	0.173	78	47	80

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>