



Angle seat check valve type 303 PVC-U With solvent cement spigots metric

Model:

- For horizontal or vertical installation
- Leakproof from: EPDM 2m, FKM 3m water column
- Specific gravity of piston approx. 2 kg/dm³
- Overall length EN 558

d (mm)	DN (mm)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)	EPDM Code	SP	Weight (kg)	FKM Code	SP	Weight (kg)
16	10	10	41	161 303 005	1	0.075	161 303 030	1	0.094
20	15	10	95	161 303 006	1	0.113	161 303 031	1	0.132
25	20	10	180	161 303 007	1	0.170	161 303 032	1	0.172
32	25	10	327	161 303 008	1	0.288	161 303 033	1	0.290
40	32	10	484	161 303 009	1	0.444	161 303 034	1	0.448
50	40	10	725	161 303 010	1	0.791	161 303 035	1	0.798
63	50	10	1130	161 303 011	1	1.345	161 303 036	1	1.345
75	65	10	1700	161 303 012	1	2.483	161 303 037	1	2.499
90	80	10	2500	161 303 013	1	3.514	161 303 038	1	3.540

d (mm)	D (mm)	H (mm)	L (mm)	L1 (mm)	L2 (mm)	closest inch (inch)
16	39	58	114	120	24	$\frac{3}{8}$
20	43	65	124	130	28	$\frac{1}{2}$
25	47	75	144	150	37	$\frac{3}{4}$
32	56	90	154	160	37	1
40	64	102	174	180	44	1 $\frac{1}{4}$
50	82	123	194	200	48	1 $\frac{1}{2}$
63	95	144	224	230	60	2
75	92	186	284	290	74	2 $\frac{1}{2}$
90	104	204	300	310	85	3

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>