



ecoFIT Bend 90° PE100 d20-500mm / SDR11

Model:

- Conventional butt-welding according to DVS 2207
- IR = Infrared-(IR Plus) compatible. Choose fusion parameters: PE100

d	DN	PN	SDR	FM	Code	Weight	L	L1	R	e	PF
(mm)	(mm)	(bar)				(kg)	(mm)	(mm)	(mm)	(mm)	
20	15	16	11	IR	753 018 706	0.007	38	23	15.00	1.9	2 68 240 006
25	20	16	11	IR	753 018 707	0.013	42	23	19.00	2.3	2 68 240 006
32	25	16	11	IR	753 018 708	0.025	46	22	24.00	2.9	2 68 240 006
40	32	16	11	IR	753 018 709	0.041	51	21	30.00	3.7	2 68 240 006
50	40	16	11	IR	753 018 710	0.065	58	21	37.00	4.6	2 68 240 006
63	50	16	11	IR	753 018 711	0.124	66	21	45.00	5.8	2 68 240 006
75	65	16	11	IR	753 018 742	0.190	75	21	71.25	6.8	
90	80	16	11	IR	753 018 743	0.325	90	22	85.50	8.2	
110	100	16	11	IR	753 018 744	0.590	110	25	104.50	10.0	
125	100	16	11	IR	753 018 715	0.818	125	28	116.00	11.4	2 68 240 002
140	125	16	11	IR	753 018 716	1.148	140	33	131.00	12.7	2 68 240 002
160	150	16	11	IR	753 018 717	1.699	160	33	151.00	14.6	2 68 240 002
180	150	16	11	IR	753 018 718	2.394	180	33	171.00	16.4	2 68 240 002
200	200	16	11	IR	753 018 719	3.264	200	33	190.00	18.2	2 68 240 002
225	200	16	11	IR	753 018 720	4.535	220	33	210.00	20.5	2 68 240 002
250	250	16	11		753 018 621	6.713	256	48	232.00	22.7	2 68 240 002
280	250	16	11		753 018 622	9.885	286	52	263.00	25.4	2 68 240 002
315	300	16	11		753 018 623	14.158	321	48	297.00	28.6	2 68 240 002
355	350	16	11		753 018 624	18.000	345	70	330.00	32.3	
400	400	16	11		753 018 625	24.020	365	70	350.00	36.3	
450	450	16	11		753 018 626	35.360	425	70	400.00	40.9	
500	500	16	11		753 018 627	47.370	470	90	445.00	45.5	

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>