


Carbon Steel Weld-on Weldolets with PVDF insert



- For use with SCH 40 metal pipe (ASTM)
- PTFE tape wetted material. Consult factory for available options.
- C - Clearance dimension
- Up to 8 in. - PVDF insert, over 8 in. - PVC insert



Type	Size (inch)	H (inch)	W (inch)	C (inch)	Sensor Type	Code	Weight (kg)
CS4W025	2.50	2.48	2.60	1.31	Flow -X0, pH -XX	198 801 464	0.500
CS4W030	3.00	2.47	2.60	1.31	Flow -X0, pH -XX	198 801 557	0.690
CS4W040	4.00	2.45	2.60	1.31	Flow -X0, pH -XX	198 801 552	0.770
CS4W050	5.00	3.24	3.50	2.10	Flow -X1	198 801 465	0.500
CS4W060	6.00	3.11	3.50	2.10	Flow -X1	198 801 553	1.490
CS4W080	8.00	2.88	3.50	2.10	Flow -X1	198 801 574	1.340
CS4W100	10.00	5.63	3.50	2.10	Flow -X2	198 801 575	1.440
CS4W120	12.00	5.40	3.50	2.10	Flow -X2	198 801 576	1.800

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>