


654 - Blue clamp saddles with stainless steel reinforcing ring, flat gasket and galvanized bolts and nuts (PN16-PN10)

- bolts and nuts : galvanized
- colour: blue
- B= N° of bolts
- M= bolt type
- (*) with O-ring gasket
- water PN16-10
- suitable for PE and PVC pipes
- female thread: ISO 7 (parallel)
- gasket: O-ring with flat lip (NBR)
- material: PP
- reinforcement ring: stainless steel AISI430

	d	Rp	PN	B	M	Code	SP	Weight	d1	L	L1	H	H1
	(mm)	(inch)	(bar)					(kg)	(mm)	(mm)	(mm)	(mm)	(mm)
*	20	½	16	2	M8X40	158 001 041	1	0.118	12	46	77	59	26
*	25	½	16	2	M8X30	158 001 042	1	0.110	13	49	79	58	15
*	25	¾	16	2	M8X30	158 001 043	1	0.110	13	49	79	58	15
*	32	½	16	2	M8X30	158 001 044	1	0.103	14	49	79	62	20
*	32	¾	16	2	M8X30	158 001 045	1	0.115	14	49	79	62	20
*	32	1	16	2	M8X40	158 001 046	1	0.151	14	62	87	70	20
	40	½	16	2	M8X40	158 001 047	1	0.135	21	62	86	71	20
	40	¾	16	2	M8X40	158 001 048	1	0.137	21	62	86	71	20
	40	1	16	2	M8X40	158 001 049	1	0.141	21	62	86	70	19
	50	½	16	4	M8X40	158 001 050	1	0.195	21	62	86	82	20
	50	¾	16	4	M8X40	158 001 051	1	0.202	21	62	86	82	20
	50	1	16	4	M8X40	158 001 052	1	0.206	21	62	86	82	20
	50	1 ¼	16	4	M8X40	158 001 053	1	0.201	21	62	86	82	20
	63	½	16	4	M8X40	158 001 054	1	0.212	18	62	101	96	21
	63	¾	16	4	M8X40	158 001 055	1	0.222	24	62	101	96	21
	63	1	16	4	M8X40	158 001 056	1	0.228	31	62	101	96	21
	63	1 ¼	16	4	M8X40	158 001 058	1	0.262	31	62	101	96	21
	63	1 ½	16	4	M8X40	158 001 057	1	0.277	31	62	101	96	21
	75	½	16	4	M8X60	158 001 059	1	0.364	16	79	123	102	14
	75	¾	16	4	M8X60	158 001 060	1	0.369	21	79	123	104	16
	75	1	16	4	M8X60	158 001 061	1	0.384	27	79	123	107	19
	75	1 ¼	16	4	M8X60	158 001 063	1	0.421	35	79	123	109	21
	75	1 ½	16	4	M8X60	158 001 062	1	0.423	42	79	123	109	21
	75	2	16	4	M8X60	158 001 064	1	0.445	53	79	123	112	24
	90	½	16	4	M8X60	158 001 065	1	0.412	16	87	138	116	14
	90	¾	16	4	M8X60	158 001 066	1	0.421	21	87	138	118	16
	90	1	16	4	M8X60	158 001 067	1	0.432	27	87	138	121	19
	90	1 ¼	16	4	M8X60	158 001 069	1	0.472	35	87	138	123	21
	90	1 ½	16	4	M8X60	158 001 068	1	0.465	42	87	138	123	21
	90	2	16	4	M8X60	158 001 070	1	0.479	53	87	138	126	24
	110	½	16	6	M8X50	158 001 071	1	0.511	15	99	152	150	23
	110	¾	16	6	M8X50	158 001 072	1	0.509	20	99	152	150	23
	110	1	16	6	M8X50	158 001 073	1	0.518	26	99	152	150	23
	110	1 ¼	16	6	M8X50	158 001 075	1	0.565	35	99	152	150	23
	110	1 ½	16	6	M8X50	158 001 074	1	0.563	41	99	152	150	23
	110	2	16	6	M8X50	158 001 076	1	0.570	51	99	152	150	23
	110	3	6	6	M8x70	158 001 077	1	1.090	85	99	152	150	23
	125	½	16	6	M8X50	158 001 078	1	0.578	15	101	166	169	24
	125	¾	16	6	M8X50	158 001 079	1	0.590	20	101	166	169	24
	125	1	16	6	M8X50	158 001 080	1	0.592	26	101	166	169	24
	125	1 ¼	16	6	M8X50	158 001 082	1	0.612	35	101	166	168	23
	125	1 ½	16	6	M8X50	158 001 081	1	0.627	41	101	166	168	23
	125	2	16	6	M8X50	158 001 083	1	0.643	50	101	166	168	23
	125	3	6	6	M8X70	158 001 084	1	1.009	85	139	178	180	37
	125	4	6	6	M8X70	158 001 085	1	1.051	90	139	178	181	38
	140	½	16	6	M8X70	158 001 086	1	0.831	18	114	207	191	25

Data sheet

valid from: 6/23/21



	d	Rp	PN	B	M	Code	SP	Weight	d1	L	L1	H	H1
	(mm)	(inch)	(bar)					(kg)	(mm)	(mm)	(mm)	(mm)	(mm)
	140	3/4	16	6	M8X70	158 001 087	1	0.832	24	114	207	191	25
	140	1	16	6	M8X70	158 001 088	1	0.836	30	114	207	191	25
	140	1 1/4	16	6	M8X70	158 001 090	1	0.869	38	114	207	191	25
	140	1 1/2	16	6	M8X70	158 001 089	1	0.858	45	114	207	191	24
	140	2	16	6	M8X70	158 001 091	1	0.883	50	114	207	191	24
	140	3	10	6	M8X70	158 001 092	1	1.091	85	142	208	201	38
	140	4	10	6	M8X70	158 001 093	1	1.123	90	142	208	201	38
	160	1/2	16	6	M8X70	158 001 094	1	0.896	18	114	226	215	24
	160	3/4	16	6	M8X70	158 001 095	1	0.875	24	114	226	215	24
	160	1	16	6	M8X70	158 001 096	1	0.915	30	114	226	215	24
	160	1 1/4	16	6	M8X70	158 001 098	1	0.935	37	114	226	215	24
	160	1 1/2	16	6	M8X70	158 001 097	1	0.933	45	114	226	215	24
	160	2	16	6	M8X70	158 001 099	1	1.021	51	114	226	215	24
	160	3	10	6	M8X70	158 001 100	1	1.013	84	142	228	222	38
	160	4	10	6	M8X70	158 001 101	1	1.262	90	142	228	222	38
*	180	1	10	6	M10X80	158 001 102	1	1.954	30	169	262	265	38
*	180	1 1/2	10	6	M10X80	158 001 103	1	1.978	54	169	262	265	38
*	180	1 1/4	10	6	M10X80	158 001 104	1	1.980	36	169	262	265	38
*	180	2	10	6	M10X80	158 001 105	1	1.995	54	169	262	265	38
*	180	3	10	6	M10X80	158 001 106	1	2.004	85	169	262	265	38
*	180	4	10	6	M10X80	158 001 107	1	2.059	103	169	262	267	40
*	200	1 1/2	10	6	M10X80	158 001 108	1	1.927	45	169	262	265	38
*	200	2	10	6	M10X80	158 001 109	1	1.948	54	169	262	265	38
*	200	3	10	6	M10X80	158 001 110	1	1.980	85	169	262	265	38
*	200	4	10	6	M10X80	158 001 111	1	2.020	103	169	262	267	40
*	225	1 1/2	10	6	M10X80	158 001 112	1	2.034	45	174	287	287	26
*	225	2	10	6	M10X80	158 001 113	1	2.050	51	174	287	287	26
*	225	3	10	6	M10X80	158 001 114	1	2.115	85	174	287	295	37
*	225	4	10	6	M10X80	158 001 115	1	2.167	103	174	287	295	38
*	250	2	10	6	M10X80	158 001 116	1	2.431	55	178	310	314	38
*	250	3	10	6	M10X80	158 001 117	1	2.383	85	178	310	314	38
*	250	4	10	6	M10X80	158 001 118	1	2.428	103	178	310	314	38
	280	2	10	6	M10X160	158 001 119	1	3.448	51	179	335	326	31
*	280	3	10	6	M10X160	158 001 120	1	3.543	78	179	335	338	41
*	280	4	10	6	M10X160	158 001 121	1	3.585	98	179	335	338	46
	315	2	10	6	M10X110	158 001 122	1	4.096	51	246	390	350	31
*	315	3	10	6	M10X110	158 001 123	1	4.267	78	246	390	363	41
*	315	4	10	6	M10X110	158 001 124	1	4.259	98	246	390	363	46

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>