



## Reducing bush ABS metric Rp

### Model:

- With solvent cement spigot metric and parallel female thread Rp
- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to ABS

| d    | Thread Type | Size   | PN    | Code               | SP | Weight | z    | D    | L    |
|------|-------------|--------|-------|--------------------|----|--------|------|------|------|
| (mm) |             | (inch) | (bar) |                    |    | (kg)   | (mm) | (mm) | (mm) |
| 20   | Rp          | 3/8    | 10    | <b>729 910 434</b> | 10 | 0.012  | 7    | 25   | 35   |
| 25   | Rp          | 1/2    | 10    | <b>729 910 437</b> | 10 | 0.017  | 7    | 30   | 41   |
| 32   | Rp          | 3/4    | 10    | <b>729 910 441</b> | 10 | 0.025  | 15   | 35   | 48   |
| 40   | Rp          | 1      | 10    | <b>729 910 446</b> | 10 | 0.046  | 20   | 45   | 56   |
| 50   | Rp          | 1 1/4  | 10    | <b>729 910 452</b> | 10 | 0.077  | 20   | 55   | 66   |
| 63   | Rp          | 1 1/2  | 10    | <b>729 910 458</b> | 5  | 0.120  | 10   | 62   | 77   |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>