




## Threaded nipple R PVC-U

### Model:

- With taper male thread R
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC-U



R (inch)	PN (bar)	Type	Code	SP	Weight (kg)	L (mm)	s (mm)
3/8	10	A	<b>721 911 905</b>	10	0.007	37	19
1/2	10	A	<b>721 911 906</b>	10	0.012	45	22
3/4	10	A	<b>721 911 907</b>	10	0.019	49	27
1	10	A	<b>721 911 908</b>	10	0.034	57	36
1 1/4	10	A	<b>721 911 909</b>	10	0.052	62	46
1 1/2	10	A	<b>721 911 910</b>	10	0.070	67	50
2	10	A	<b>721 911 911</b>	10	0.126	76	65

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>