



## PROGEF Plus Reducer SDR11 (PN10)

### Model:

- Cleaned and double bagged
- Conventional butt-welding according to DVS 2207
- IR = Infrared welding compatible
- Material: PP-H

| d    | SDR | PN    | d1   | FM | Code        | Weight | L    | L1   | L2   | e    | e1   |
|------|-----|-------|------|----|-------------|--------|------|------|------|------|------|
| (mm) |     | (bar) | (mm) |    |             | (kg)   | (mm) | (mm) | (mm) | (mm) | (mm) |
| 25   | 11  | 10    | 20   | IR | 727 908 637 | 0.008  | 50   | 20   | 20   | 2.3  | 1,9  |
| 32   | 11  | 10    | 20   | IR | 727 908 642 | 0.012  | 50   | 20   | 20   | 2.9  | 1,9  |
| 32   | 11  | 10    | 25   | IR | 727 908 641 | 0.013  | 50   | 20   | 20   | 2.9  | 2,3  |
| 40   | 11  | 10    | 20   | IR | 727 908 648 | 0.015  | 58   | 20   | 23   | 3.7  | 1,9  |
| 40   | 11  | 10    | 25   | IR | 727 908 647 | 0.017  | 55   | 20   | 20   | 3.7  | 2,3  |
| 40   | 11  | 10    | 32   | IR | 727 908 646 | 0.019  | 55   | 20   | 20   | 3.7  | 2,9  |
| 50   | 11  | 10    | 25   | IR | 727 908 654 | 0.026  | 60   | 20   | 20   | 4.6  | 2,3  |
| 50   | 11  | 10    | 32   | IR | 727 908 653 | 0.026  | 60   | 20   | 20   | 4.6  | 2,9  |
| 50   | 11  | 10    | 40   | IR | 727 908 652 | 0.032  | 60   | 20   | 20   | 4.6  | 3,7  |
| 63   | 11  | 10    | 32   | IR | 727 908 660 | 0.046  | 65   | 20   | 20   | 5.8  | 2,9  |
| 63   | 11  | 10    | 40   | IR | 727 908 659 | 0.048  | 65   | 20   | 20   | 5.8  | 3,7  |
| 63   | 11  | 10    | 50   | IR | 727 908 658 | 0.051  | 65   | 20   | 20   | 5.8  | 4,6  |
| 75   | 11  | 10    | 40   | IR | 727 908 666 | 0.063  | 68   | 20   | 20   | 6.8  | 3,7  |
| 75   | 11  | 10    | 50   | IR | 727 908 665 | 0.072  | 65   | 20   | 20   | 6.8  | 4,6  |
| 75   | 11  | 10    | 63   | IR | 727 908 664 | 0.079  | 65   | 20   | 20   | 6.8  | 5,8  |
| 90   | 11  | 10    | 63   | IR | 727 908 671 | 0.119  | 75   | 22   | 19   | 8.2  | 5,8  |
| 90   | 11  | 10    | 75   | IR | 727 908 670 | 0.131  | 75   | 21   | 19   | 8.2  | 6,8  |
| 110  | 11  | 10    | 63   | IR | 727 908 672 | 0.201  | 90   | 28   | 28   | 10.6 | 6,2  |
| 110  | 11  | 10    | 75   | IR | 727 908 677 | 0.211  | 90   | 28   | 18   | 10.0 | 6,8  |
| 110  | 11  | 10    | 90   | IR | 727 908 676 | 0.231  | 90   | 28   | 20   | 10.0 | 8,2  |
| 125  | 11  | 10    | 110  | IR | 727 908 680 | 0.325  | 100  | 31   | 30   | 11.4 | 10,0 |
| 140  | 11  | 10    | 110  | IR | 727 908 685 | 0.430  | 110  | 33   | 29   | 12.7 | 10,0 |
| 140  | 11  | 10    | 125  | IR | 727 908 684 | 0.468  | 110  | 34   | 30   | 12.7 | 11,4 |
| 160  | 11  | 10    | 110  | IR | 727 908 690 | 0.595  | 120  | 38   | 27   | 14.6 | 10,0 |
| 160  | 11  | 10    | 140  | IR | 727 908 688 | 0.652  | 120  | 40   | 35   | 14.6 | 12,7 |
| 180  | 11  | 10    | 90   | IR | 727 908 780 | 0.800  | 145  | 50   | 40   | 16.4 | 8,2  |
| 180  | 11  | 10    | 110  | IR | 727 908 781 | 1.010  | 150  | 50   | 40   | 16.4 | 10,0 |
| 180  | 11  | 10    | 125  | IR | 727 908 782 | 0.985  | 145  | 52   | 40   | 16.4 | 11,4 |
| 180  | 11  | 10    | 140  | IR | 727 908 783 | 0.995  | 135  | 51   | 47   | 16.4 | 12,7 |
| 180  | 11  | 10    | 160  | IR | 727 908 784 | 1.020  | 135  | 55   | 52   | 16.4 | 14,6 |
| 200  | 11  | 10    | 160  | IR | 727 908 692 | 1.120  | 145  | 50   | 40   | 18.2 | 14,6 |
| 200  | 11  | 10    | 180  | IR | 727 908 785 | 1.300  | 145  | 50   | 45   | 18.2 | 16,4 |
| 225  | 11  | 10    | 110  | IR | 727 908 695 | 1.489  | 160  | 55   | 35   | 20.5 | 10,0 |
| 225  | 11  | 10    | 160  | IR | 727 908 696 | 1.590  | 160  | 55   | 40   | 20.5 | 14,6 |
| 225  | 11  | 10    | 180  | IR | 727 908 786 | 1.770  | 163  | 60   | 58   | 20.5 | 16,4 |
| 225  | 11  | 10    | 200  | IR | 727 908 697 | 1.650  | 160  | 55   | 50   | 20.5 | 18,2 |
| 250  | 11  | 10    | 160  | IR | 727 908 787 | 2.140  | 170  | 63   | 53   | 22.7 | 14,6 |
| 250  | 11  | 10    | 225  | IR | 727 908 788 | 2.750  | 180  | 65   | 65   | 22.7 | 20,5 |
| 280  | 11  | 10    | 225  | IR | 727 908 789 | 3.425  | 203  | 72   | 57   | 25.4 | 20,5 |
| 280  | 11  | 10    | 250  | IR | 727 908 790 | 1.980  | 206  | 75   | 60   | 25.4 | 22,7 |
| 315  | 11  | 10    | 225  | IR | 727 908 791 | 5.110  | 237  | 84   | 60   | 28.6 | 20,5 |
| 315  | 11  | 10    | 250  | IR | 727 908 792 | 5.105  | 231  | 86   | 63   | 28.6 | 22,7 |
| 315  | 11  | 10    | 280  | IR | 727 908 793 | 5.130  | 222  | 80   | 70   | 28.6 | 25,4 |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

# Data sheet

valid from: 7/22/21

---



Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>