



Metal - butterfly valve type 039M With hand lever

Model:

- Body GGG40 (A 395 / A395 M-99, EN-JIS 1020 EN1563) Rilsan® coating
- Seat material: EPDM, FKM and others on request
- Single-piece axis with square profile, up to DN 600 mm 2-pieces axis
- Installation length: EN 558 row 20
- Mounting between ISO, ANSI, BS or JIS Flanges
- Interface according to DIN EN ISO 5211

Option:

- Electric and pneumatic actuator on request

d	Size	DN	PN	kv-value	Disc: ductile	SP	Weight	Disc:	SP	Weight
(mm)	(inch)	(mm)	(bar)	($\Delta p=1$ bar)	iron/Rilsan®		(kg)	stainless		(kg)
				(l/min)	coated			steel EPDM		
					EPDM			Code		
					Code					
63	2	50	16	3167	199 039 000	1	4.000	199 039 200	1	4.000
75	2 ½	65	16	4667	199 039 001	1	4.700	199 039 201	1	4.700
90	3	80	16	7167	199 039 002	1	5.000	199 039 202	1	5.000
110	4	100	16	11833	199 039 003	1	6.400	199 039 203	1	6.400
140	5	125	16	18333	199 039 004	1	8.200	199 039 204	1	8.200
160	6	150	16	26667	199 039 005	1	9.700	199 039 205	1	9.700
225	8	200	16	46667	199 039 006	1	14.300	199 039 206	1	14.300
280	10	250	16	78333	199 039 007	1	25.200	199 039 207	1	25.200
315	12	300	16	115000	199 039 008	1	36.000	199 039 208	1	34.100

d	Disc: Alu- bronze	SP	Weight	H	H1	H2	H3	L	L1	L2	Cv val- ue ($\Delta p=1$ psi)	d3
(mm)	EPDM		(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(l/min)	(mm)
	Code											
63	199 039 400	1	4.000	290	53	140	95	43	45	220	837	95
75	199 039 401	1	4.700	312	63	152	95	46	45	220	1233	114
90	199 039 402	1	5.000	327	71	159	95	46	45	220	1893	131
110	199 039 403	1	6.400	360	87	178	95	52	45	220	3126	152
140	199 039 404	1	8.200	388	102	191	95	56	45	320	4843	182
160	199 039 405	1	9.700	416	118	203	95	56	45	320	7045	209
225	199 039 406	1	14.300	489	149	245	95	60	45	320	12328	262
280	199 039 407	1	25.200	525	200	275	50	68	63	560	20693	331
315	199 039 408	1	34.100	592	227	315	50	78	63	560	30380	380

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>