



**Double union safe block ball valve PVC-U  
With solvent cement sockets Inch BS**

d (mm)	DN (mm)	d (inch)	PN (bar)	EPDM Code	SP	Weight (kg)
	15	3/8	16	<b>VSA22L160</b>	150	0.126
	15	1/2	16	<b>VSA22L200</b>	150	0.129
	20	3/4	16	<b>VSA22L250</b>	100	0.201
	25	1	16	<b>VSA22L320</b>	60	0.286
	32	1 1/4	16	<b>VSA22L400</b>	36	0.433
	40	1 1/2	16	<b>VSA22L500</b>	24	0.703
	50	2	16	<b>VSA22L630</b>	13	1.175
75	65	2 1/2	10	<b>VSA22I750</b>	8	2.200
	80	3	10	<b>VSA22L900</b>	4	3.310
	100	4	10	<b>VSA22L910</b>	2	5.864

L1 (mm)	L2 (mm)	S (mm)	H1 (mm)	A (mm)	H2 (mm)	X (mm)	M (mm)	Z (mm)	H (mm)
		19	14	50	76	42	40	48	53
		19	16	50	80	42	40	48	53
		19	19	59	91	48	45	53	60
		21	22	68	102	54	51	58	67
		25	26	80	120	62	59	68	79
		27	31	94	140	72	70	78	90
		29	38	115	169	86	84	93	107
44	206	32	44	145	206	110	103	118	129
		36	51	168	242	128	120	140	143
		43	61	210	282	150	141	160	169

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>