



PROGEF Standard
3-Way ball valve type 543
Horizontal/L-port
With fusion sockets metric

Model:

- Material: PP-H
- For easy installation and removal (valve end and union nut are compatible with type 546)
- Ball seals PTFE
- Pneumatic or electric actuator available separately
- Angle of operation 360° without turn limiter
- Turn limiter 90° enclosed, in different positions usable as a clip-on ring
- Integrated stainless steel mounting inserts
- Delivery status A-C opened, see flow scheme

d	DN	PN	kv-value	EPDM	Weight	FKM	Weight
(mm)	(mm)	(bar)	($\Delta p=1$ bar)	Code	(kg)	Code	(kg)
			(L/min)				
16	10	10	50	167 543 001	0.161	167 543 011	0.161
20	15	10	75	167 543 002	0.165	167 543 012	0.165
25	20	10	150	167 543 003	0.237	167 543 013	0.237
32	25	10	280	167 543 004	0.374	167 543 014	0.361
40	32	10	480	167 543 005	0.616	167 543 015	0.616
50	40	10	620	167 543 006	0.950	167 543 016	0.912
63	50	10	1230	167 543 007	1.843	167 543 017	1.882

d	D	H	H1	H2	L	L1	L2	L3	L4	L5	L6	M	z	z1	closest
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	inch
															(inch)
16	50	57	28	8	110	77	72	36	25	32	45	6	82	41	$\frac{3}{8}$
20	50	57	28	8	112	77	72	36	25	32	45	6	82	41	$\frac{1}{2}$
25	58	67	32	8	129	97	85	43	25	39	58	6	97	49	$\frac{3}{4}$
32	68	73	36	8	146	97	98	49	25	39	58	6	110	55	1
40	84	90	45	9	170	128	118	59	45	54	74	8	132	66	$1\frac{1}{4}$
50	97	97	51	9	193	128	135	68	45	54	74	8	151	76	$1\frac{1}{2}$
63	124	116	65	9	244	152	176	88	45	66	87	8	188	94	2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>