

Rotor Kit, O-ring, Cable for 2540 Hot-Tap

MFR #	Description	Code	Weight (kg)	For Type
3-1500.663	Hot-Tap Install. Tool	198 820 008	1.700	2540
1220-0021	O-ring, FKM (2 req'd per sensor)	198 801 000	0.001	515, 2536, 2537
1224-0021	O-ring, EPR (EPDM) (2 req'd per sensor)	198 820 006	0.002	515, 2536, 2537
1228-0021	O-ring, FFPM (2 req'd per sensor)	198 820 007	0.004	515, 2536, 2537
3-2540.320	Rotor Kit/(old)	198 820 040	0.050	2540
3-2540.321	Rotor Kit, Tungsten Carbide Pin	159 000 623	0.050	2540
3-2540.520	Bearing, Fluoroloy B®/PTFE	159 000 648	0.001	2540
P52527	Retainers, Stainless steel	159 000 481	0.001	525, 2540
3-2541.260-1	Standard module	159 000 849	0.100	2540
3-2541.260-2	Hot-Tap module	159 000 850	0.100	2540
P51589	Conduit Adapter Kit	159 000 476	0.050	515, 2536
P31934	Conduit Cap	159 000 466	0.100	515, 2536
3-2540.322	Rotor kit, Stainless steel pin and rotor	159 000 864	0.020	
P52504-3	Rotor pin, Tungsten Carbide	159 000 866	0.001	
P52504-4	Rotor pin, 316 SS	159 000 867	0.001	
P52503	Bearing, carbon reinforced PTFE	198 820 013	0.040	525

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>