



316 SS (1.4401) Threaded Tees with NPT Threads with PVDF insert

- For use with SCH 40 metal pipe (ASTM)
- PTFE tape wetted material. Consult factory for available options.
- PVDF insert - all sizes

Type	Size (inch)	L (inch)	H (inch)	Sensor Type	Code	Weight (kg)
CR4T005	0.50	3.60	4.00	Flow -X0, pH -XX	198 801 554	0.410
CR4T007	0.75	3.60	4.20	Flow -X0, pH -XX	198 801 555	0.460
CR4T010	1.00	3.60	4.20	Flow -X0, pH -XX	198 801 556	0.400
CR4T012	1.25	3.80	4.50	Flow -X0, pH -XX	198 801 783	0.450
CR4T015	1.50	4.10	4.80	Flow -X0, pH -XX	198 801 784	0.500
CR4T020	2.00	4.90	5.30	Flow -X0, pH -XX	198 801 785	0.800

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>