


MULTI/JOINT® 3207 Plus Wide Range
end cap threaded, restraint, Uni/Fiksers
A4

Model:


- Suitable for all kinds of pipe material
- Suitable for water and gas
- Ductile cast iron GGG45 body and clamping ring(s), acc. to EN-GJS-450-10
- RESICOAT® epoxy powder coating, according to GSK standards and EN 14901
- NBR or EPDM gasket, NBR acc. to EN 682 (-5°C up to +50°C), EPDM acc. to EN 681-1 (0°C up to +50°C)
- Angular deflection of max. 8° per socket at installation (based on the middle of the range)
- Stainless steel A4 quality (AISI 316) Uni/Fiksers
- Stainless steel A2 quality (AISI 304) or A4 quality (AISI 316) bolts, nuts and washers
- For restraint versions, on plastic pipes, the use of an insert stiffener (see accessories) is mandatory, check our technical information
- Hygiene protection included DN50 - DN600



DN (mm)	Range 1 (mm)	Rp (inch)	NBR / A4 Code	EPDM / A4 Code	Weight (kg)
50	46 - 71	¾	709 385 004	709 385 304	3.500
50	46 - 71	1	709 385 005	709 385 305	3.500
50	46 - 71	1 ¼	709 385 006	709 385 306	3.500
50	46 - 71	1 ½	709 385 007	709 385 307	3.500
50	46 - 71	2	709 385 008	709 385 308	3.500
65	63 - 90	¾	709 385 009	709 385 309	4.100
65	63 - 90	1	709 385 010	709 385 310	4.100
65	63 - 90	1 ¼	709 385 011	709 385 311	4.100
65	63 - 90	1 ½	709 385 012	709 385 312	4.100
65	63 - 90	2	709 385 013	709 385 313	4.100
80	84 - 105	¾	709 385 014	709 385 314	5.100
80	84 - 105	1	709 385 015	709 385 315	5.100
80	84 - 105	1 ¼	709 385 016	709 385 316	5.100
80	84 - 105	1 ½	709 385 017	709 385 317	5.100
80	84 - 105	2	709 385 018	709 385 318	5.100
100	104 - 132	¾	709 385 019	709 385 319	6.500
100	104 - 132	1	709 385 020	709 385 320	6.500
100	104 - 132	1 ¼	709 385 021	709 385 321	6.500
100	104 - 132	1 ½	709 385 022	709 385 322	6.500
100	104 - 132	2	709 385 023	709 385 323	6.500
125	132 - 155	¾	709 385 024	709 385 324	7.800
125	132 - 155	1	709 385 025	709 385 325	7.800
125	132 - 155	1 ¼	709 385 026	709 385 326	7.800
125	132 - 155	1 ½	709 385 027	709 385 327	7.800
125	132 - 155	2	709 385 028	709 385 328	7.800
150	154 - 192	¾	709 385 029	709 385 329	9.600
150	154 - 192	1	709 385 030	709 385 330	9.600
150	154 - 192	1 ¼	709 385 031	709 385 331	9.600
150	154 - 192	1 ½	709 385 032	709 385 332	9.600
150	154 - 192	2	709 385 033	709 385 333	9.600
200	192 - 232	¾	709 385 034	709 385 334	18.300
200	192 - 232	1	709 385 035	709 385 335	18.300
200	192 - 232	1 ¼	709 385 036	709 385 336	18.300
200	192 - 232	1 ½	709 385 037	709 385 337	18.300
200	192 - 232	2	709 385 038	709 385 338	18.300
225	230 - 268	¾	709 385 049	709 385 349	20.900
225	230 - 268	1	709 385 050	709 385 350	20.900
225	230 - 268	1 ¼	709 385 051	709 385 351	20.900
225	230 - 268	1 ½	709 385 052	709 385 352	20.900
225	230 - 268	2	709 385 053	709 385 353	20.900
250	267 - 310	¾	709 385 039	709 385 339	27.100
250	267 - 310	1	709 385 040	709 385 340	27.100
250	267 - 310	1 ¼	709 385 041	709 385 341	27.100

Data sheet

valid from: 7/5/17




DN (mm)	Range 1 (mm)	Rp (inch)	NBR / A4 Code	EPDM / A4 Code	Weight (kg)
250	267 - 310	1 ½	709 385 042	709 385 342	27.100
250	267 - 310	2	709 385 043	709 385 343	27.100
300	315 - 356	¾	709 385 044	709 385 344	34.400
300	315 - 356	1	709 385 045	709 385 345	34.400
300	315 - 356	1 ¼	709 385 046	709 385 346	34.400
300	315 - 356	1 ½	709 385 047	709 385 347	34.400
300	315 - 356	2	709 385 048	709 385 348	34.400
400	392 - 433	¾	709 385 054	709 385 354	43.100
400	392 - 433	1	709 385 055	709 385 355	43.100
400	392 - 433	1 ¼	709 385 056	709 385 356	43.100
400	392 - 433	1 ½	709 385 057	709 385 357	43.100
400	392 - 433	2	709 385 058	709 385 358	43.100

DN (mm)	a (mm)	b (mm)	d (mm)	e (mm)	PN Water (bar)	PN Gas (bar)
50	115 - 130	164	100	3xM12	16.0	8
50	115 - 130	164	100	3xM12	16.0	8
50	115 - 130	164	100	3xM12	16.0	8
50	115 - 130	164	100	3xM12	16.0	8
50	115 - 130	164	100	3xM12	16.0	8
65	145 - 157	186	95	3xM12	16.0	8
65	145 - 157	186	95	3xM12	16.0	8
65	145 - 157	186	95	3xM12	16.0	8
65	145 - 157	186	95	3xM12	16.0	8
65	145 - 157	186	95	3xM12	16.0	8
80	142 - 156	204	115	3xM12	16.0	8
80	142 - 156	204	115	3xM12	16.0	8
80	142 - 156	204	115	3xM12	16.0	8
80	142 - 156	204	115	3xM12	16.0	8
80	142 - 156	204	115	3xM12	16.0	8
100	144 - 163	236	110	3xM16	16.0	8
100	144 - 163	236	110	3xM16	16.0	8
100	144 - 163	236	110	3xM16	16.0	8
100	144 - 163	236	110	3xM16	16.0	8
100	144 - 163	236	110	3xM16	16.0	8
125	151 - 169	264	120	4xM16	16.0	8
125	151 - 169	264	120	4xM16	16.0	8
125	151 - 169	264	120	4xM16	16.0	8
125	151 - 169	264	120	4xM16	16.0	8
125	151 - 169	264	120	4xM16	16.0	8
150	149 - 177	304	120	4xM16	16.0	8
150	149 - 177	304	120	4xM16	16.0	8
150	149 - 177	304	120	4xM16	16.0	8
150	149 - 177	304	120	4xM16	16.0	8
200	180 - 207	354	140	6xM16	16.0	8
200	180 - 207	354	140	6xM16	16.0	8
200	180 - 207	354	140	6xM16	16.0	8
200	180 - 207	354	140	6xM16	16.0	8
200	180 - 207	354	140	6xM16	16.0	8
225	211 - 242	386	145	6xM20	16.0	8
225	211 - 242	386	145	6xM20	16.0	8
225	211 - 242	386	145	6xM20	16.0	8
225	211 - 242	386	145	6xM20	16.0	8
225	211 - 242	386	145	6xM20	16.0	8
250	214 - 249	432	170	6xM20	16.0	8
250	214 - 249	432	170	6xM20	16.0	8
250	214 - 249	432	170	6xM20	16.0	8
250	214 - 249	432	170	6xM20	16.0	8

Data sheet

valid from: 7/5/17



DN (mm)	a (mm)	b (mm)	d (mm)	e (mm)	PN Water (bar)	PN Gas (bar)
250	214 - 249	432	170	6xM20	16.0	8
300	219 - 254	490	170	8xM20	16.0	8
300	219 - 254	490	170	8xM20	16.0	8
300	219 - 254	490	170	8xM20	16.0	8
300	219 - 254	490	170	8xM20	16.0	8
300	219 - 254	490	170	8xM20	16.0	8
400	253 - 295	574	205	10xM20	10.0	5
400	253 - 295	574	205	10xM20	10.0	5
400	253 - 295	574	205	10xM20	10.0	5
400	253 - 295	574	205	10xM20	10.0	5
400	253 - 295	574	205	10xM20	10.0	5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>