



Tank adaptor type 050 PVC-U Compact

Model:

- End connection: solvent cement socket, metric
- Gasket: flat gasket EPDM
- Washer: PP
- Run-out holes: two holes in octagonal head
- FKM flat gasket available for tank adaptor type 050

d (mm)	PN (bar)	EPDM Code	SP	Weight (kg)
16	16	161 050 445	75	0.048
20	16	161 050 446	50	0.066
25	16	161 050 447	70	0.170
32	16	161 050 448	50	0.144
40	16	161 050 449	30	0.238
50	16	161 050 450	20	0.260
63	16	161 050 451	15	0.398

d (mm)	L3 max (mm)	Diameter of bore in tank side (mm)	D1 (mm)	S (mm)	D (mm)	L2 (mm)	S1 (mm)	L4 (mm)	L1 (mm)	d2 (mm)	G (inch)
16	28	28	29	32	44	11	40	14	58	5	3/4
20	28	35	35	40	54	12	50	16	61	5	1
25	28	43	42	50	60	13	55	19	65	5	1 1/4
32	28	49	49	56	69	13	65	22	67	5	1 1/2
40	29	61	59	69	84	13	80	26	72	5	2
50	30	67	70	76	92	15	85	31	76	5	2 1/4
63	35	83	82	95	108	15	100	38	84	5	2 3/4

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>