


Check valve type 561ABS
Without spring
With solvent cement sockets metric

Model:

- Sealing at a minimum water column of 2 m
- Designed for easy installation and removal
- Vibration free even at high flow velocity
- Flow-optimized return cone, double guided
- For vertical installation
- Compact installation length, same as ball valve type 546
- Z-length, end connectors and union nuts **not** compatible with type 360
- New DN65-DN100



d	DN	Size	PN	kv-value	EPDM	SP	Weight
(mm)	(mm)	(inch)	(bar)	($\Delta p=1$ bar)	Code		(kg)
				(l/min)			
16	10	3/8	10	190	169 561 001	1	0.090
20	15	1/2	10	180	169 561 002	1	0.090
25	20	3/4	10	380	169 561 003	1	0.190
32	25	1	10	460	169 561 004	1	0.220
40	32	1 1/4	10	850	169 561 005	1	0.380
50	40	1 1/2	10	1080	169 561 006	1	0.560
63	50	2	10	1670	169 561 007	1	0.990
75	65	2 1/2	10	2950	169 561 008	1	2.420
90	80	3	10	3600	169 561 009	1	3.870
110	100	4	10	4150	169 561 010	1	6.240

d	D	L	L2	z	closest
(mm)	(mm)	(mm)	(mm)	(mm)	inch
					(inch)
16	50	92	56	64	3/8
20	50	95	56	64	1/2
25	58	110	65	72	3/4
32	68	123	71	79	1
40	84	146	85	94	1 1/4
50	97	157	89	95	1 1/2
63	124	183	101	107	2
75	166	233	136	144	2 1/2
90	200	254	141	151	3
110	238	301	164	174	4

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>