



Rubber sealed tapping saddle PVC-U
d63-225mm / With integral cutter / Outlet with PVP thread

- 1 bar Gas / 10 bar Water
- No standard thread
- For PVC pipes for tapping under operating pressure
- Hexagon KEY for tapping: 799 150 008 (32 - 40 mm); 799 150 009 (50 - 63 mm)
- NBR sealing

d (mm)	PN (bar)	DN (mm)	Thread Type	Code	SP	Weight (kg)	d1 (mm)	Connection	Tapping-Ø (mm)	L (mm)
63	10	50	G	161 114 409	1	1.228	32	1	21	105
75	10	65	G	161 114 415	1	1.150	32	1	30	105
90	10	80	G	161 114 422	1	1.198	32	1	30	105
110	10	100	G	161 114 430	1	1.486	32	1	30	105
110	10	100	G	161 114 433	1	1.473	63	2	39	105
160	10	150	G	161 114 454		1.398	32	1	30	120
160	10	150	G	161 114 457	1	2.351	63	2	39	120
225	10	200	G	161 114 470	1	2.023	32	1	30	120
225	10	200	G	161 114 473	1	2.503	63	2	39	120

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>