



Throttle valve type V251 PVC-U
With solvent cement sockets metric

d	Size	DN	PN	EPDM	SP	Weight	FKM	SP	Weight
(mm)	(inch)	(mm)	(bar)	Code		(kg)	Code		(kg)
16	¾	10	10	199 041 203		0.048	199 041 210		0.048
20	½	15	10	199 041 204		0.077	199 041 211		0.081
25	¾	20	10	199 041 205		0.123	199 041 212		0.122
32	1	25	10	199 041 206		0.217	199 041 213		0.219
40	1 ¼	32	10	199 041 207		0.352	199 041 214		0.329
50	1 ½	40	10	199 041 208		0.662	199 041 215	1	0.662
63	2	50	10	199 041 209		1.213	199 041 216		1.213

d	D	H	H1	L	closest
(mm)	(mm)	(mm)	(mm)	(mm)	inch
16	29	57	45	47	¾
20	35	66	51	55	½
25	40	80	63	66	¾
32	47	96	75	80	1
40	56	111	86	100	1 ¼
50	70	133	101	120	1 ½
63	88	158	118	146	2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>