



Profiled backing flange steel metric
For butt fusion systems metric

Model:

- PP with glass-fibre reinforcement and GGG 50 insert
- Connecting dimensions: ISO 7005, EN 1092, DIN 2501
- **Bolt circle PN 10**

Note:

Flat side = bolt / washer side

Profiled side = flange adaptor side (aligned with collar)

AL: number of holes

* Galvanized steel S235-JR, suitable for underground laying

	d	DN	PN	Code	SP	Weight	D	D1	D2	D3	H	AL	SC
	(mm)	(mm)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)	(mm)		
*	450	450	10	724 705 026	1	38.000	615	565	470	26	36	20	M24
	450	500	10	724 700 426	1	25.600	685	620	517	26	56	20	M24
	500	500	10	724 700 427	1	21.061	685	620	533	26	56	20	M24
	560	600	10	724 700 428	1	35.000	796	725	618	30	68	20	M27
	630	600	10	724 700 429	1	28.500	800	725	645	30	68	20	M27
	710	700	6	724 700 430	1	25.500	912	840	740	30	49	24	M27
	800	800	6	724 700 431	1	39.300	1026	950	843	33	58	24	M30
	900	900	6	724 700 432	1	48.500	1129	1050	947	33	62	28	M30

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>