






PROGEF Standard 3-Way ball valve type 543
Horizontal/T-port
With lockable handle
With butt fusion spigots IR-Plus SDR11 metric

Model:

- Material: PP-H
- For easy installation and removal (valve end and union nut are compatible with type 546)
- Ball seals PTFE
- Pneumatic or electric actuator available separately
- Angle of operation 360° without turn limiter
- Turn limiter 90° enclosed, in different positions usable as a clip-on ring
- Integrated stainless steel mounting inserts
- Multifunctional lever red with ratched setting 45°, lockable
- Delivery status A-B-C opened, see flow scheme



d	DN	Size	PN	kv-value	EPDM	SP	Weight	FKM	SP	Weight
(mm)	(mm)	(inch)	(bar)	(Δp=1 bar)	Code		(kg)	Code		(kg)
20	15	½	10	200	167 543 622	1	0.179	167 543 632	1	0.179
25	20	¾	10	470	167 543 623	1	0.257	167 543 633	1	0.257
32	25	1	10	793	167 543 624	1	0.389	167 543 634	1	0.384
40	32	1 ¼	10	1290	167 543 625	1	0.637	167 543 635	1	0.637
50	40	1 ½	10	1910	167 543 626	1	0.954	167 543 636	1	0.954
63	50	2	10	3100	167 543 627	1	1.846	167 543 637	1	1.846

d	D	H	H1	H2	L	L1	L2	L3	L4	L5	L6	M	e	closest
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	inch
20	50	79	28	8	146	87	72	36	25	42	45	6	2	½
25	58	88	32	8	163	108	85	43	25	50	58	6	2	¾
32	68	94	36	8	178	108	98	49	25	50	58	6	3	1
40	84	113	45	9	204	141	118	59	45	66	75	8	4	1 ¼
50	97	119	51	9	237	141	135	68	45	66	75	8	5	1 ½
63	124	141	65	9	296	165	176	88	45	78	87	8	6	2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>