



Union end PVC-U metric

Model:

- Solvent cement socket metric
- Suitable for unions, tank connectors and diaphragm valves Type 514

* Must **not** be used for unions 721 510 112, 721 510 313 and 721 510 137, 721 510 338, only suitable for Variable area flow meter

d (mm)	PN (bar)	Code	SP	Weight (kg)	z (mm)	D (mm)	D1 (mm)	L (mm)
10	16	721 500 103	10	0.004	3	20	18	15
12	16	721 500 104	10	0.003	3	20	18	15
16	16	721 500 105	10	0.003	3	24	22	17
20	16	721 500 106	10	0.008	3	30	28	19
25	16	721 500 107	10	0.014	3	39	36	22
32	16	721 500 108	10	0.020	3	45	42	25
40	16	721 500 109	10	0.037	3	57	53	29
50	16	721 500 110	10	0.039	3	63	59	34
63	16	721 500 111	10	0.072	3	78	74	41
75	10	721 500 162	20	0.140	3	101	90	47
90	10	721 500 163	12	0.242	5	121	108	56
110	10	721 500 164	10	0.390	5	146	131	66
*	75	721 600 112	110	0.155	3	97	90	47
*	90	721 600 113	0	0.188	5	110	105	56

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>