

6.3. Raccords Filetés - Taraudés

6.3.1. Raccords Filetés - Taraudés en laiton nickelé

LAITON

Caractéristiques :

- Pression d'utilisation : **-0,99 à 60 bar**
- Température de service du fluide : **-10°C à +150°C**

Mamelon conique - BSPT Mâle



Référence	Ø Racc.
2102001	1/8" - 1/8"
2102002	1/8" - 1/4"
2102003	1/8" - 3/8"
2102004	1/4" - 1/4"
2102005	1/4" - 3/8"
2102006	1/4" - 1/2"
2102007	3/8" - 3/8"
2102008	3/8" - 1/2"
2102009	1/2" - 1/2"
2102010	1/2" - 3/4"
2102011	3/4" - 3/4"
8000007	3/4" - 1"
8000008	1" - 1"

Grossisseur cylindrique - BSPP Mâle-Femelle



Référence	Ø Racc.
2152001	M5 - 1/8"
2152002	1/8" - 1/8"
2152003	1/8" - 1/4"
2152004	1/4" - 1/4"
2152005	1/4" - 3/8"
2152006	3/8" - 3/8"
2152007	3/8" - 1/2"
2152008	1/2" - 1/2"

Manchon égal - BSPP Femelle-Femelle



Référence	Ø Racc.
2103000	M5
2103001	1/8"
2103002	1/4"
2103003	3/8"
2103004	1/2"
8000010	1"

Réduction conique - BSPT Mâle - BSPP Femelle



Référence	Ø Racc.
2104001	1/4" - 1/8"
2104002	3/8" - 1/8"
2104003	3/8" - 1/4"
2104004	1/2" - 1/4"
2104005	1/2" - 3/8"
2104006	3/4" - 1/2"
FTNB.006.0114	1" - 1/4"
8000014	1" - 3/8"
8000015	1" - 1/2"
8000016	1" - 3/4"
FTNB.006.0212	2" - 1/2"

Manchon inégal - BSPP Femelle-Femelle



Référence	Ø Racc.
2106001	1/8" - 1/4"
2106002	1/8" - 3/8"
2106003	1/4" - 3/8"
2106004	1/4" - 1/2"
2106005	3/8" - 1/2"

Grossisseur conique - BSPT Mâle - BSPP Femelle



Référence	Ø Racc.
2105001	1/8" - 1/8"
2105002	1/8" - 1/4"
2105003	1/4" - 1/4"
2105004	1/4" - 3/8"
2105005	3/8" - 3/8"
2105006	3/8" - 1/2"
2105007	1/2" - 1/2"

Bouchon cylindrique avec o-ring NBR - Mâle



Référence	Ø Racc.
2107000	M5
2107001	1/8"
2107002	1/4"
2107003	3/8"
2107004	1/2"
8000018	3/4"
8000019	1"
FTNB.007.0202	2"
FTNB.007.0303	3"

Coude - BSPP Femelle-Femelle



Référence	Ø Racc.
2109001	1/8" - 1/8"
2109002	1/4" - 1/4"
2109003	3/8" - 3/8"
2109004	1/2" - 1/2"