



Pressure pilot valve type PV95 3/2-ways

- For direct installation on single acting pneumatic actuators (FC/F0)
- Hollow screw
- Circuit function C: de-energized closed
- Port A: actuator connection
- Port P: compressed air
- Power consumption: 24VA at AC inrush; 17VA/8W at AC hold; 8W at DC
- Connector plug form A
- Valve material: polyamid/brass

Compressed air connec- tion P	Actuator connec- tion A	Voltage	DN (mm)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)
NPT 1/8	G 1/4	24 V=	2	10	120
NPT 1/8	G 1/4	110 V, 50-60 Hz	2	10	120
G 1/4	G 1/8	24 V=	2	10	120
G 1/4	G 1/8	24 V, 50-60 Hz	2	10	120
G 1/4	G 1/8	110 V, 50-60 Hz	2	10	120
G 1/4	G 1/8	230 V, 50-60 Hz	2	10	120

NBR Code	SP	Weight (kg)
199 190 554	1	0.487
199 190 555	1	0.409
199 190 532	1	0.479
199 190 533	1	0.406
199 190 534	1	0.473
199 190 535	1	0.435

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>