



Rubber sealed branch saddle PVC-U
d63-225mm / Outlet with solvent cement socket

- 1 bar Gas / 10 bar Water
- NBR sealing

d	DN	PN	Code	SP	Weight	d1	d2	L
(mm)	(mm)	(bar)			(kg)	(mm)	(mm)	(mm)
63	50	10	161 111 035	1	0.697	40	22	105
63	50	10	161 111 036	1	0.733	50	22	105
75	65	10	161 111 046	1	0.778	50	31	105
90	80	10	161 111 055	1	0.829	40	31	105
90	80	10	161 111 056	1	0.867	50	31	105
110	100	10	161 111 065	1	0.935	40	31	105
110	100	10	161 111 066	1	0.970	50	40	105
110	100	10	161 111 067	1	1.003	63	40	105
160	150	10	161 111 095	1	1.252	40	31	120
160	150	10	161 111 096	1	1.281	50	40	120
160	150	10	161 111 097	1	1.488	63	40	120
225	200	10	161 111 116	1	1.587	50	40	120
225	200	10	161 111 117	1	1.756	63	40	120

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>