



Shrink socket PE

Model:

- For a water- and steam-tight sealing in combination with buthylene rubber-based sealing tape
- Length: 100 mm
- "Heavy duty" version for high end applications
- For connections of the same pipe outer diameter

d (mm)	D (mm)	Code	SP	Weight (kg)	L (mm)
25 - 32	90	738 011 013	0	0.100	100
40 - 50	110	738 011 014	0	0.113	100
63	125	738 011 015	0	0.133	100
75	140	738 011 016	0	0.146	100
90	160	738 011 017	0	0.165	100
110	180	738 011 018	0	0.222	100
140	225	738 011 020	0	0.280	100
160	250	738 011 021	0	0.352	100
200	280	738 011 022	0	0.371	100
225	315	738 011 023	0	0.444	100
250	355	738 011 024	1	0.900	100
280	400	738 011 025	1	1.100	100
315	450	738 011 026	1	1.900	100
355	500	738 011 027	1	1.000	100
400	560	738 011 028	1	1.000	100
450	630	738 011 029	1	1.000	100

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>