






3-Way ball valve type 543 PVC-C
Horizontal/T-port
With lockable handle
With solvent cement sockets metric

Model:

- For easy installation and removal (valve end and union nut are compatible with type 546)
- Ball seals PTFE
- Pneumatic or electric actuator available separately
- Angle of operation 360° without turn limiter
- Turn limiter 90° enclosed, in different positions usable as a clip-on ring
- Integrated stainless steel mounting inserts
- Multifunctional lever red with ratched setting 45°, lockable
- Delivery status A-B-C opened, see flow scheme



d	DN	Size	PN	kv-value	EPDM	SP	Weight	FKM	SP	Weight
(mm)	(mm)	(inch)	(bar)	(Δp=1 bar)	Code		(kg)	Code		(kg)
16	10	3/8	10	140	163 543 401	1	0.280	163 543 411	1	0.280
20	15	1/2	10	200	163 543 402	1	0.286	163 543 412	1	0.286
25	20	3/4	10	470	163 543 403	1	0.408	163 543 413	1	0.408
32	25	1	10	793	163 543 404	1	0.609	163 543 414	1	0.609
40	32	1 1/4	10	1290	163 543 405	1	1.031	163 543 415	1	1.031
50	40	1 1/2	10	1910	163 543 406	1	1.512	163 543 416	1	1.512
63	50	2	10	3100	163 543 407	1	2.923	163 543 417	1	2.923

d	D	H	H1	H2	L	L1	L2	L3	L4	L5	L6	M	z	z1	closest
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)		(mm)	(mm)	inch
16	50	79	28	8	109	87	73	36	25	42	45	6	81	40	3/8
20	50	79	28	8	112	87	73	36	25	42	45	6	81	40	1/2
25	58	88	32	8	131	108	86	43	25	50	58	6	94	47	3/4
32	68	94	36	8	151	108	99	50	25	50	58	6	107	54	1
40	84	113	45	9	181	141	120	60	45	66	75	8	130	65	1 1/4
50	97	119	51	9	205	141	137	69	45	66	75	8	143	72	1 1/2
63	124	141	65	9	261	165	179	89	45	78	87	8	185	92	2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Data sheet

valid from: 8/20/21



Internet: <http://www.gfps.com>
