

SYGEF Plus tee 90° reduced SDR21/PN16
High Purity clean-room product ISO Class 5 (100)

Model:


- Material: PVDF-HP

	d - d1 (mm)	SDR	PN (bar)	FM	Code	SP	GP	Weight (kg)
A	63 - 20	21	16	BCF, IR	735 208 956	1	15	0.250
A	63 - 25	21	16	BCF, IR	735 208 957	1	20	0.245
A	63 - 32	21	16	BCF, IR	735 208 958	1	15	0.257
A	63 - 40	21	16	BCF, IR	735 208 959	1	15	0.254
A	75 - 20	21	16	BCF, IR	735 208 961	1	6	0.348
A	75 - 25	21	16	BCF, IR	735 208 962	1	10	0.356
A	75 - 32	21	16	BCF, IR	735 208 963	1	6	0.308
A	75 - 40	21	16	BCF, IR	735 208 964	1	10	0.312
A	75 - 50	21	16	BCF, IR	735 208 965	1	10	0.372
A	90 - 20	21	16	BCF, IR	735 208 967	1	10	0.470
A	90 - 25	21	16	BCF, IR	735 208 968	1	10	0.466
A	90 - 32	21	16	BCF, IR	735 208 969	1	10	0.405
A	90 - 40	21	16	BCF, IR	735 208 970	1	10	0.476
A	90 - 50	21	16	BCF, IR	735 208 971	1	10	0.452
B	90 - 63	21	16	BCF, IR	735 208 972	1	8	0.611
A	110 - 20	21	16	BCF, IR	735 208 974	1	8	0.641
A	110 - 25	21	16	BCF, IR	735 208 975	1	8	0.570
A	110 - 32	21	16	BCF, IR	735 208 976	1	8	0.570
A	110 - 40	21	16	BCF, IR	735 208 977	1	8	0.640
A	110 - 50	21	16	BCF, IR	735 208 978	1	5	0.640
B	110 - 63	21	16	BCF, IR	735 208 979	1	5	0.925
B	110 - 75	21	16	BCF, IR	735 208 980	1	5	0.950
B	110 - 90	21	16	BCF, IR	735 208 981	1	5	0.959
B	160 - 90	21	16	IR	735 208 687	1	2	2.902
B	160 - 110	21	16	IR	735 208 686	1	2	3.078
B	225 - 90	21	16	IR	735 208 695	1	1	5.423
B	225 - 110	21	16	IR	735 208 694	1	1	5.460


	d - d1 (mm)	e (mm)	e1 (mm)	L (mm)	L1 (mm)	L2 (mm)	L3 (mm)
A	63 - 20	3.0	1.9	60	67	25	35
A	63 - 25	3.0	1.9	60	66	25	34
A	63 - 32	3.0	2.4	60	67	25	25
A	63 - 40	3.0	2.4	60	66	25	26
A	75 - 20	3.6	1.9	65	69	25	31
A	75 - 25	3.6	1.9	65	72	25	34
A	75 - 32	3.6	2.4	65	69	25	31
A	75 - 40	3.6	2.4	65	72	25	26
A	75 - 50	3.6	3.0	65	69	25	26
A	90 - 20	4.3	1.9	65	76	25	31
A	90 - 25	4.3	1.9	65	79	25	34
A	90 - 32	4.3	2.4	65	76	25	31
A	90 - 40	4.3	2.4	65	79	25	26
A	90 - 50	4.3	3.0	65	76	25	26
B	90 - 63	4.3	3.0	80	85	25	25
A	110 - 20	5.3	1.9	65	86	25	31
A	110 - 25	5.3	1.9	65	89	25	34
A	110 - 32	5.3	2.4	65	86	25	31
A	110 - 40	5.3	2.4	65	89	25	26
A	110 - 50	5.3	3.0	65	86	25	26
B	110 - 63	5.3	3.0	90	95	30	25
B	110 - 75	5.3	3.0	90	95	30	25
B	110 - 90	5.3	4.3	90	95	30	25

Data sheet

valid from: 8/23/21



	d - d1	e	e1	L	L1	L2	L3
	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
B	160 - 90	7.7	4.3	155	130	60	25
B	160 - 110	7.7	5.3	155	130	60	25
B	225 - 90	10.8	4.3	155	160	60	25
B	225 - 110	10.8	5.3	155	160	60	25



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>