




COOL-FIT 4.0 T90° reduced d32-d225

Model:

- Pre-insulated PE100 SDR11, metric
- Insulation made from GF HE foam
- Outer jacket impact resistant. Color: black
- A: Electrofusion Fitting with integrated sealing lip, for a water and vapour tight sealing
- *Available as long as stocks last



DN (mm)	d/D (mm)	d1/D1 (mm)	SDR	PN (bar)	Code	Weight (kg)	
65	75/140	63/125	11	16	738 203 218	0.863	
80	90/160	63/125	11	16	738 203 222	1.232	
80	90/160	75/140	11	16	738 203 223	1.293	
100	110/180	63/125	11	16	738 203 227	1.972	
100	110/180	75/140	11	16	738 203 228	1.949	
100	110/180	90/160	11	16	738 203 229	2.037	
*	150	160/250	63/125	11	16	738 203 247	5.150
*	150	160/250	90/160	11	16	738 203 249	5.147
*	150	160/250	110/180	11	16	738 203 250	5.220
150	160/250	140/200	11	16	738 204 251	5.540	
200	225/315	63/125	11	16	738 203 264	16.832	
200	225/315	90/160	11	16	738 203 266	16.889	
200	225/315	110/180	11	16	738 203 267	16.805	
200	225/315	140/200	11	16	738 204 268	17.100	
200	225/315	160/250	11	16	738 203 269	18.500	
150	160/250	63/125	11	16	738 203 447	4.250	
150	160/250	90/160	11	16	738 203 449	4.420	
150	160/250	110/180	11	16	738 203 450	4.590	

	D2 (mm)	L (mm)	L1 (mm)	L2 (mm)	z (mm)	z1 (mm)	Closest inch (inch)	Type
	147	116	55	48	36	228	2 ½	A
	168	130	62	48	43	253	3 - 2	A
	168	130	62	55	43	252	3 - 2 ½	A
	188	154	72	48	57	267	4 - 2	A
	188	154	72	55	57	268	4 - 2 ½	A
	188	154	72	62	57	268	4 - 3	A
*	258	192	90	48	77	327	6 - 2	A
*	258	192	90	62	77	327	6 - 3	A
*	258	192	90	72	77	325	6 - 5	A
	258	192	90	84	77	340	6 - 5	A
	324	355	110	48	220	412	8 - 2	A
	324	355	110	62	220	412	8 - 3	A
	324	355	110	72	220	412	8 - 4	A
	324	335	110	84	220	412	8 - 5	A
	324	355	110	90	220	396	8 - 6	A
	258	192	90	48	77	221	6 - 1	
	258	192	90	62	77	235	6 - 3	
	258	192	90	72	77	245	6 - 5	

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Data sheet

valid from: 9/13/21



Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>