




Solenoid pilot valve type MNL532
3/2 & 5/2-ways for single and double acting actuators
with NAMUR interface

Model:

- With NAMUR connection and two silencers/throttle screws

Mode of action:

- 3/2-way valve, in rest position pressure inlet 1 closed, outlet 3 exhausted
- 5/2-way valve, in rest position pressure inlet 1 connected to outlet 4, outlet 3 exhausted
- Material of body: Aluminum
- Electrical connection: cable plug
- **to pneumatic actuators**

Voltage	Size (inch)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)	Compressed air connection P	DN (mm)	NBR Code	SP	Weight (kg)
230 V, AC	1/4	10	950	G 1/4	5	199 190 360	1	0.332
110 V, AC	1/4	10	950	G 1/4	5	199 190 359	1	0.343
48 V, AC	1/4	10	950	G 1/4	5	199 190 361	1	0.341
24 V, AC	1/4	10	950	G 1/4	5	199 190 358	1	0.339
24 V, DC	1/4	10	950	G 1/4	5	199 190 357	1	0.343

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>