



PROGEF Natural Reducer SDR11 (PN10)

Model:

- Material: PP-R unpigmented
- Bead and Crevice Free weldable with the new BCF® Plus fusion machine
- Infrared-(IR Plus®) compatible. Choose fusion parameters: PP-n (PP-R)
- Conventional butt-welding according to DVS 2207

d	SDR	PN	d1	FM	Code	Weight	L	L1	L2	e	e1
(mm)		(bar)	(mm)			(kg)	(mm)	(mm)	(mm)	(mm)	(mm)
25	11	10	20	BCF, IR	728 908 537	0.007	50	20	20	2.3	1.9
32	11	10	20	BCF, IR	728 908 542	0.010	50	20	20	3.0	1.9
32	11	10	25	BCF, IR	728 908 541	0.011	50	20	20	3.0	2.3
40	11	10	20	BCF, IR	728 908 548	0.015	58	20	23	3.7	1.9
40	11	10	25	BCF, IR	728 908 547	0.016	55	20	20	3.7	2.3
40	11	10	32	BCF, IR	728 908 546	0.019	55	20	20	3.7	2.9
50	11	10	25	BCF, IR	728 908 554	0.025	60	20	20	4.6	2.3
50	11	10	32	BCF, IR	728 908 553	0.027	60	20	20	4.6	2.9
50	11	10	40	BCF, IR	728 908 552	0.030	60	20	20	4.6	3.7
63	11	10	32	BCF, IR	728 908 560	0.043	65	20	20	5.8	2.9
63	11	10	40	BCF, IR	728 908 559	0.047	65	20	20	5.8	3.7
63	11	10	50	BCF, IR	728 908 558	0.052	65	20	20	5.8	4.6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>