



INSTAFLEX Adapter union PB/Brass Socket / Female thread

Including EPDM O-Ring, quality suitable for potable water

d (mm)	Rp (inch)	Code	SP	Weight (kg)	Code	PF	L (mm)	z1 (mm)	z2 (mm)	G (inch)
16	½	761 066 705	10	0.164	760 857 162	2 21 050 201	45	8	9	1
20	½	761 066 706	10	0.219	760 857 163	2 21 050 201	47	8	10	1 1/4
25	¾	761 066 707	10	0.268	760 857 164	2 21 050 201	50	8	9	1 1/2
32	1	761 066 708	5	0.270	760 857 165	2 21 050 201	53	8	8	2
40	1 ¼	761 066 709	5	0.600	760 857 166	2 21 050 201	58	10	7	2 1/2
50	1 ½	761 066 710	2	0.700	760 857 167	2 21 050 201	61	10	7	2 3/4
63	2	761 066 711	2	0.950	760 857 168	2 21 050 201	66	10	9	3 1/2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>