



INSTAFLEX Valve BTV 2 PB

- Material: PB, brass, gunmetal
- Brass: UBA conform
- Gasket: EPDM, approved for potable hot and cold water
- Electro fusion quality for portable water

d (mm)	DN (mm)	Code	SP	Weight (kg)	D (mm)	L (mm)	H (mm)	z (mm)	Value (Zeta)	kv-100-value ($\Delta p=1$ bar) (l/min)
20	15	761 069 647	1	0.425	55	86	112	47	0.4	421
25	20	761 069 648	1	0.427	55	89	112	47	0.4	421
32	25	761 069 649	1	0.470	55	94	112	52	0.4	421
40	32	761 069 650	1	1.237	90	112	165	65	0.3	1291
50	40	761 069 651	1	1.369	90	120	165	71	0.3	1291
63	50	761 069 652	1	1.851	90	141	165	90	0.3	1291

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>