




## Plug PVC-U G

### Model:

- With parallel male thread G
- Flat gasket necessary for sealing
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC-U



Thread Type	Size (inch)	PN (bar)	Code	SP	Weight (kg)	L (mm)	s (mm)
G	3/8	10	<b>721 960 905</b>	10	0.005	21	22
G	1/2	10	<b>721 960 906</b>	10	0.010	25	27
G	3/4	10	<b>721 960 907</b>	10	0.018	29	36
G	1	10	<b>721 960 908</b>	10	0.029	32	41
G	1 1/4	10	<b>721 960 909</b>	10	0.048	36	50
G	1 1/2	10	<b>721 960 910</b>	10	0.070	37	60
G	2	10	<b>721 960 911</b>	5	0.120	42	75

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>